



Item # 20017572, PYROFLEX HOT TAR WAND Transfer Hose 1 in x 400 ft, 300 psi, Black

APPLICATION: A high quality wand hose used in asphalt crack filling applicator and dispensing service.

CONSTRUCTION TUBE: Black Nitrile (special heat resistance)

COVER: Black Wingprene® (wrapped finish) flame-retardant

REINFORCEMENT: Spiral-plied (2) steel wire

TEMPERATURE: -25 °F to 350 °F (-32 °C to 177 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING (SPIRAL): Example: Continental Contitech Pyroflex Hot Tar Wand Hose.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Petrol Transfer
Style	Petrol Transfer Hose
Construction Tube	Black Nitrile (special heat resistance)
Cover	Black Wingprene® (wrapped finish) flame-retardant
Reinforcement	Spiral-plied (2) steel wire
Color	Black
Min. Temperature	-25 °F 350 °C

Max. Temperature	-32 °F 177 °C
Max. Working Pressure	300.0 psi 2.07 MPa
Brand	PYROFLEX® HOT TAR WAND
Packaging	Coiled, Polywrapped
Order Code	543-118

Specifications

I.D.	1 in 25.40 mm
Nom. O.D.	1.610 in 40.90 mm
Total Width	1.610 in 40.90 mm
Length	400.000 ft
Weight	0.840 lb/ft 1.25 kg/m

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech