



Item # 20013127, SPIRATHANE LD Abrasive / Corrosive Hose 4 in x 100 ft, 15 psi

APPLICATION: For dry pneumatic conveying of solid fines where abrasion is present and service conditions are moderate. Excellent for low-pressure blowing applications.

CONSTRUCTION TUBE: Clear Polyurethane, RMA Class B (Medium Oil Resistance)

REINFORCEMENT: High-density rigid white Pliovic® helix

TEMPERATURE: 0 °F to 158 °F (-18 °C to 70 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Not branded



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Abrasive Transfer
Style	Abrasive / Corrosive Hose
Construction Tube	Clear Polyurethane, RMA Class B (Medium Oil Resistance)
Reinforcement	High-density rigid white Pliovic® helix
Color	Clear/White
Min. Temperature	0 °F -18 °C
Max. Temperature	158 °F 70 °C

Max. Working Pressure	15.0 psi 0.10 MPa
Brand	SPIRATHANE™ LD
Order Code	586-406

Specifications

I.D.	4 in 101.60 mm
Nom. O.D.	4.530 in 115.10 mm
Total Width	4.530 in 115.10 mm
Length	100.000 ft
Bend Radius	7.000 in 178.00 mm
Vacuum Rating	13.000 inHg 330.00 mmHg
Weight	0.880 lb/ft 1.31 kg/m

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech