



Item # 20012480, SPIRAFLEX 2700 YELLOW HEAVY DUTY Water Discharge Hose 6 in x 300 ft, 150 psi, Yellow

APPLICATION: For heavy-duty applications in mining, agriculture, construction and marine service. Limited oil and chemical application.

CONSTRUCTION TUBE: Black Pliovic® /Nitrile PVC Tube

COVER: Yellow fire-retardant Pliovic, MSHA 2G-14C/15

REINFORCEMENT: Synthetic fabric

TEMPERATURE: -10 °F to 150 °F (-23 °C to 66 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Example: Continental Contitech Spiraflex® Yellow 2" (50.8 mm), 200 psi (1.38 MPa) Flame Resistant, USMSHA 2G-14C/15. Made in USA.

Note: Working pressures are rated at 72 °F.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Water Transfer
Style	Water S & D Hose
Construction Tube	Black Pliovic® /Nitrile PVC Tube

Cover	Yellow fire-retardant Pliovic, MSHA 2G-14C/21
Reinforcement	Synthetic fabric
Color	Yellow
Min. Temperature	-10 °F -23 °C
Max. Temperature	150 °F 66 °C
Max. Working Pressure	150.0 psi 1.03 MPa
Brand	SPIRAFLEX® 2700 YELLOW HEAVY DUTY
Order Code	537-513

Specifications

I.D.	6 in 152.40 mm
Nom. O.D.	6.480 in 164.60 mm
Total Width	6.480 in 164.60 mm
Length	300.000 ft
Weight	1.690 lb/ft 2.51 kg/m

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech