ContiTech Products



## Item # 20022595, INSTA-GRIP TC Air & Multipurpose Push-on Hose 5/16 in x 500 ft, 300 PSI, Black

**APPLICATION:** For low-pressure hydraulic and pneumatic systems such as shop air systems, general industrial, maintenance and automotive assembly applications.

**CONSTRUCTION TUBE:** Chemivic<sup>™</sup> oil- and heat-resistant synthetic rubber, RMA Class A (High Oil Resistance)

COVER: Black, dyed textile braid, mildew- and oil-resistant

**REINFORCEMENT:** Braided (1) high-strength synthetic yarn laid at an angle for strength and coupling holding ability

TEMPERATURE: -40 °F to 190 °F (-40 °C to 88 °C)

**COUPLINGS:** Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

**BRANDING:** Example: Insta-Grip<sup>™</sup> TC 3/8" 300 psi WP. Made in USA Continental Contitech.



## Product Specifications | Specifications

Proc	luct S	Specif	licatio	ne

Туре	Push-on Transfer	
Style	Hydraulic Hose	
Construction Tube	Chemivic™ oil- and heat-resistant synthetic rubber, RMA Class A (High Oil Resistance)	
Cover	Black, dyed textile braid, mildew- and oil-resistant	
Reinforcement	Braided (1) high-strength synthetic yarn laid at an angle for strength and coupling holding ability	

12/26/2017 | Page 2 of 2

Color	Black
Min. Temperature	-40 °F -40 °C
Max. Temperature	190 °F 88 °C
Max. Working Pressure	300.0 psi 2.07 MPa
Brand	INSTA-GRIP™
Packaging	Reel
Order Code	535-230

## Specifications

I.D.	5/16 in 7.90 mm
Nom. O.D.	0.560 in 14.20 mm
Total Width	0.560 in 14.20 mm
Length	500.000 ft
Bend Radius	3.000 in 76.00 mm
Weight	0.090 lb/ft 0.13 kg/m

MideastUS@contitech.uss 1-800-235-4632 Contitech.us

## ContiTech