



Item # 20019167, 250 STEAM Hose 3/4 in x 50 ft, 250 PSI, Red/Yellow

APPLICATION: A rugged construction used for all-around steam service in chemical plants, refineries, shipyards and demanding industrial service. It is recommended for cleaning, thawing, blowout service, steam pumps, hoists and other applications involving steam.

CONSTRUCTION TUBE: Black EPDM(compound)® synthetic rubber

COVER: Black EPDM(compound)® synthetic rubber, also available in red cover with yellow brand for color coding (wrapped impression)

REINFORCEMENT: Spiral-plied steel wire

TEMPERATURE: 0 °F to 406 °F (-18 °C to 208 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING (SPIRAL): Example: Continental Contitech Plicord® Steam 250 psi. Drain after use.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Steam Transfer
Style	Steam Transfer Hose
Construction Tube	Black Versigard® synthetic rubber
Cover	Red Versigard® synthetic rubber with yellow brand for color coding (wrapped impression)
Reinforcement	Spiral-plied steel wire

Color	Red/Yellow
Min. Temperature	0 °F -18 °C
Max. Temperature	406 °F 208 °C
Max. Working Pressure	250.0 psi 1.72 MPa
Brand	PLICORD® 250 STEAM
Order Code	549-061

Specifications

I.D.	3/4 in 19.10 mm
Nom. O.D.	1.250 in 31.80 mm
Total Width	1.250 in 31.8 mm
Length	50.000 ft
Weight	0.490 lb/ft 0.73 kg/m

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech