



Item # 20146823, PLIOVIC GS Multipurpose Hose 1/4" MNPT 3/8 in x 50 ft, 250 PSI, Blue

APPLICATION: A lightweight, economical general purpose hose for carrying air, water and many spray solutions. Pliovic® is suitable for a wide range of industrial, construction, agricultural hand sprayers and many multipurpose applications. Nonconductive, minimum electrical resistance greater than one (1) megohm per inch of hose length at 1000 Volts DC. Available in Pliovic® GS construction or a thick cover, Pliovic® Plus construction. Non-marking cover.

CONSTRUCTION TUBE: Black Pliovic®, RMA Class B (Medium Oil Resistance)

COVER: Pliovic®, smooth finish, RMA Class B (Medium Oil Resistance)

REINFORCEMENT: Spiral synthetic yarn

TEMPERATURE: -10 °F to 158 °F (-23 °C to 70 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Example: Pliovic® GS 3/8" ID (9.5 mm) 250 psi WP. Made in USA. Continental Contitech



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Multipurpose Transfer
Style	Multipurpose Hose
Reinforcement	Spiral synthetic yarn
Cover	PlioVic®, smooth finish, RMA Class B (Medium Oil Resistance)
Construction Tube	Black PlioVic®, RMA Class B (Medium Oil Resistance)

Color	Blue
Min. Temperature	-10 °F -23 °C
Max. Temperature	158 °F 70 °C
Max. Working Pressure	250.0 psi 1.72 MPa
Packaging	Coil
Brand	PLIOVIC®
Order Code	540-350
Edited By: Initials and Date	SAS 11/27/12

Specifications

I.D.	3/8 in 9.50 mm
Nom. O.D.	0.660 in 16.80 mm
Length	50.000 ft
Weight	0.130 lb/ft 0.19 kg/m

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech