



Item # 20025994, INSTA-GRIP 250 Air & Multipurpose Push-on Hose 3/8 in x 500 ft, 250 PSI, Red

APPLICATION: For use with push-on fittings at working pressures of 250 psi for industrial service. Nonconductive, minimum electrical resistance greater than one (1) megohm per inch of hose length at 1000 Volts DC.

CONSTRUCTION TUBE: Chemivic™ oil- and heat-resistant synthetic rubber, RMA Class A (High Oil Resistance)

COVER: Red, Black, or Green Chemivic™, RMA Class B (Medium Oil Resistance)

REINFORCEMENT: Spiral Flexten® yarn

TEMPERATURE: -20 °F to 190 °F (-29 °C to 88 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Example: Insta-Grip™ Nonconductive 3/8" (9.5 mm) 250 psi WP. Made in USA Continental Contitech.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Air and Multipurpose Transfer
Style	Air and Multipurpose Hose
Reinforcement	Spiral Flexten® yarn
Cover	Red Chemivic™, RMA Class B (Medium Oil Resistance)
Construction Tube	Chemivic™ oil- and heat-resistant synthetic rubber, RMA Class A (High Oil Resistance)

Color	Red
Min. Temperature	-20 °F 190 °C
Max. Temperature	-29 °F 88 °C
Max. Working Pressure	250.0 psi 1.72 MPa
Packaging	Reel
Brand	INSTA-GRIP™
Order Code	569-013

Specifications

I.D.	3/8 in 9.50 mm
Nom. O.D.	0.650 in 16.50 mm
Length	500.000 ft
Weight	0.120 lb/ft 0.18 kg/m

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech