



Item # 20018906, XF BLAST (2 Ply) Abrasive / Corrosive Hose 1/2 in x 50 ft, 150 psi, Black

APPLICATION: Standard-duty hose for steel shot or sand blasting in cleaning or finishing metal, stone, glass or other surfaces.

CONSTRUCTION TUBE: CHEMITUF(compound)® synthetic rubber (static dissipating/static conductive)

COVER: Black SBR(compound)® synthetic rubber (static dissipating/static conductive) (wrapped impression)

REINFORCEMENT: Spiral-plied synthetic fabric

TEMPERATURE: -25 °F to 180 °F (-32 °C to 82 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING (SPIRAL): Example: Continental Contitech XF Blast 150 psi WP.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Abrasive Transfer
Style	Abrasive / Corrosive Hose
Construction Tube	Tufsyn® synthetic rubber (static dissipating/static conductive)
Cover	Black Plioflex® synthetic rubber (static dissipating/static conductive) (wrapped impression)
Reinforcement	Spiral-plied synthetic fabric

Color	Black
Min. Temperature	-25 °F -32 °C
Max. Temperature	180 °F 82 °C
Max. Working Pressure	150.0 psi 1.03 MPa
Brand	PLICORD® XF BLAST (2 Ply)
Order Code	549-018

Specifications

I.D.	1/2 in 12.70 mm
Nom. O.D.	1.128 in 28.65 mm
Length	50.000 ft
Weight	0.370 lb/ft

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech