

GRUJ Conduit Outlet Boxes with Multiple Hubs

Explosionproof, Dust-Ignitionproof

UNILETS® for use with Threaded Metal Conduit.

Class I, Division 1 and 2, Groups C, D
Class II, Division 1 and 2, Groups E, F, G
Class III

Applications

- Complies with a wide range of classified area requirements.
- Corrosion-resistant: ideal indoors or out.
- For pulling of wires.
- Connect conduit lengths and change direction of conduit runs.
- Provide access for maintenance.

Features

- Malleable iron bodies have high tensile strength and ductility. Provides great resistance to corrosion, impact, and shock.
- Accurately tapped, tapered hub threads for tight, rigid joints and ground continuity.
- Furnished with covers.
- General purpose wiring.
- Union hubs permit easy wiring.
- Externally threaded body with internally threaded cover.
- Smooth, rounded integral bushing in each hub type box protects conductor insulation.

Standard Materials

- Bodies and covers: malleable iron

Standard Finishes

- Bodies and covers: triple-coat — (1) zinc electroplate, (2) chromate, and (3) epoxy powder coat

Certifications and Compliances

- UL Standard: UL 886 (UL 1203)
- UL Listed: E10444

	Number and Size of Hubs				Capacity in ³ /dm ³	Catalog Number
	Each Side	Top	Bottom	Back		
GRUJ Box with Cover						
<i>Externally threaded malleable iron body complete with internally threaded malleable iron surface cover; choice of hub arrangements, furnished with close-up plugs for all but three 3/4" hubs. Cover opening—3.25"/82.6 mm</i>						
	2 — 3/4"	2 — 3/4"	1 — 3/4"	None	25.0/0.41	GRUJ-1P
	2 — 3/4"	2 — 3/4"	1 — 3/4"	4 — 3/4"	25.0/0.41	GRUJ-2P
	2 — 3/4"	2 — 3/4"	1 — 3/4"	4 — 1"	25.0/0.41	GRUJ-3P
GRU Covers						
<i>Malleable iron with internal threads. Cover opening—3.25"/82.6 mm.</i>						
	Surface					GRUK-S

Dimensions

