

A-51® Incandescent Factory Sealed Luminaire Accessories

For Group C and D Locations. Explosionproof

Suitable for use in Wet Locations. UNILETS for use with Threaded Metal Conduit.

Type	Fixture Size		Catalog Number			
Standard Dome						
 16.00"/406.4 mm Porcelain	 16.00"/406.4 mm Polyester	(Not for use with short brackets) 60-100 W (AAU-1N) 150-300 W (AAU-15N) 200-300 W (AAU-2NS)	Porcelain AARW-15ST AARW-15ST AARW-2ST	Polyester — — AARP-2ST		
30° Angle						
 12.00"/304.8 mm Porcelain	 12.00"/304.8 mm Polyester	60-100 W (AAU-1N) 150-300 W (AAU-15N) 200-300 W (AAU-2NS)	AARW-15AN AARW-15AN AARW-2AN	— — AARP-2AN		
Colored Glass Globes						
		Amber 60-100 W (AAU-1N) 150-300 W (AAU-15N) 200-300 W (AAU-2NS)	AAGL-1A AAGL-1A AAGL-2A			
		Green 60-100 W (AAU-1N) 150-300 W (AAU-15N) 200-300 W (AAU-2NS)	AAGL-1G AAGL-1G AAGL-2G			
		Red 60-100 W (AAU-1N) 150-300 W (AAU-15N) 200-300 W (AAU-2NS)	AAGL-1R AAGL-1R AAGL-2R			
		Replacement Socket				
		 AASP-22	 AASP-44	60-100 W (AAU-1N) — Medium Base 150-300 W (AAU-15N) — Medium Base 200-300 W (AAU-2NS) — Medium Base	AASP-11 AASP-22 AASP-22	
		Connection Block				
				Fits A-51 Mounting Hoods 60-300 W	VPT-7	
		Globe Gaskets — Fiber and Aluminum				
				Requires one of each 60-300 W (AAU-1N and AAU-15N) 200-300 W (AAU-2NS)	Fiber AASP-15V AASP-2V	Aluminum AASP-15A AASP-2A

LIGHTING: EXPLOSIONPROOF — AREA — INCANDESCENT

Lighting