

AHG and UNJ Flexible Fixture Hangers

Malleable Iron. Ball Type.:15° Swing. Cushion Type: 8° Swing

UNILETS® for Use with Threaded Rigid Metal Conduit and IMC.

Applications

- AHG cushion hangers are enclosed and gasketed—ideal where dust and dampness are present.

Features

- All hangers
 - All fixture hangers protect fixture against wind and vibration damage.
 - Cushion type for added protection where lighting fixtures are subjected to vibration.
- AHG hangers
 - Enclosed and gasketed.
 - Neoprene diaphragm keeps moisture and dirt out of system.
 - Cushion type permits 8° swing from vertical.
- UNJ hangers
 - Economical general purpose hanger.
 - Permits 15° swing.

Standard Materials

- AHG fixture hangers: malleable iron
- UNJ fixture hangers: malleable iron and steel

Standard Finishes

- AHG: triple-coat—(1) zinc electroplate, (2) chromate, and (3) epoxy powder coat
- UNJ: malleable iron and steel parts, zinc electroplate and clear chromate

Certifications and Compliances

- CSA Certified: 065180 (UNJ)
- UL Listed: E109438 (AWG)



AHG5050




UNJ-50

Illustrated Features



Lighting

LIGHTING: FLEXIBLE FIXTURE HANGERS – ORDINARY LOCATION

	Fixture Stem Size (Inches)	Male Nipple Size (Inches)	Length A in/mm	Support Weight (lbs/kg)	Catalog Number
AHG – Fixture Hangers – Cushion Type – Enclosed and Gasketed – Cushions 40 lbs./18.0 kg.					
 <p>Cushion</p>	1/2	1/2	3.19/81.0	40/18	AHG5050
	1/2	3/4	3.19/81.0		AHG7550
	3/4	3/4	3.19/81.0		AHG7575
UNJ – Fixture Hangers – Malleable Iron and Steel – Ball Type					
 <p>Ball</p>	1/2	1/2	4.00/101.6	120/54	UNJ-50
	3/4	3/4	4.00/101.6		UNJ-75