

Compression Lug Splices

Short Barrel



Features

- Seamless, high conductivity copper tubing, suitable for heavy duty applications
- Tin-plated to provide corrosion resistance
- Color coded

Applications

- Suitable for use at voltages up to 35 KV provided connector is properly taped
- 5 KV is the maximum voltage in all bare splice applications




Standard Material

- Copper

Standard Finish

- Tin plated



Catalog Number	UPC	Wire Size	Color Code	Unit Carton	Ship Case	Weight/Case	Inches	
							A	B
3301	81599	#8	Red	100	1000	12	.90	.17
3302	81600	#6	Blue	100	1000	14	1	.20
3303	81601	#4	Gray	100	1000	16	1	.25
3305	81602	#2	Brown	100	1000	27	1.25	.31
3305A	81603	#1	Green	50	500	23	1.60	.39
3306	81604	1/0	Pink	50	500	26	1.75	.44
3307	81605	2/0	Black	50	500	29	1.75	.49
3308	81606	3/0	Orange	50	500	34	1.90	.55
3309	81607	4/0	Purple	25	250	23	2	.59
3309A	81608	250 MCM	Yellow	25	250	29	2.10	.66
3310	81609	350 MCM	Red	20	200	31	2.10	.70
3310A	81610	400 MCM	Blue	10	100	21	2.30	.76
3311	81611	500 MCM	Brown	10	100	29	2.50	.83
3311A	81612	600 MCM	Green	5	50	20	2.50	.93
3312	81613	750 MCM	Black	5	50	29	3.21	1.03