

# Rigid Couplings

## Tubular Threaded Type - Aluminum

### Features

- Rigid aluminum couplings are available from 1/2" thru 4"
- Manufactured from 6063 Aluminum Alloy for lightweight and corrosion resistant protection
- NPSM threads
- UL listed, UL6 / ANSI C80.5

### Application


- For use with aluminum rigid conduit or elbows in a harsh or clean environment, such as waste-water treatment, food processing, oil refineries, paper mills, and power plants

### Standard Material

- 6063 aluminum alloy



UL listed UL 6 and ANSI C80.5



| Catalog Number | UPC   | Size          | Outside Diameter | Threads Per Inch | Ship Case | Weight/ Case | Inches |      |
|----------------|-------|---------------|------------------|------------------|-----------|--------------|--------|------|
|                |       |               |                  |                  |           |              | A      | B    |
| <b>51AL</b>    | 87230 | <b>1/2"</b>   | 1.08"            | 14               | 150       | 6            | 1.08   | 1.67 |
| <b>52AL</b>    | 87231 | <b>3/4"</b>   | 1.33"            | 14               | 50        | 5            | 1.33   | 1.69 |
| <b>53AL</b>    | 87232 | <b>1"</b>     | 1.56"            | 11-1/2           | 30        | 4            | 1.56   | 1.97 |
| <b>54AL</b>    | 87233 | <b>1-1/4"</b> | 1.95"            | 11-1/2           | 25        | 5            | 1.95   | 2.07 |
| <b>55AL</b>    | 87234 | <b>1-1/2"</b> | 2.22"            | 11-1/2           | 25        | 6            | 2.22   | 2.11 |
| <b>56AL</b>    | 87235 | <b>2"</b>     | 2.75"            | 11-1/2           | 20        | 7            | 2.75   | 2.14 |
| <b>57AL</b>    | 87236 | <b>2-1/2"</b> | 3.28"            | 8                | 12        | 7            | 3.28   | 3.24 |
| <b>58AL</b>    | 87237 | <b>3"</b>     | 3.97"            | 8                | 8         | 7            | 3.97   | 3.31 |
| <b>59AL</b>    | 87238 | <b>3-1/2"</b> | 4.44"            | 8                | 4         | 4            | 4.44   | 3.41 |
| <b>60AL</b>    | 87239 | <b>4"</b>     | 5.00"            | 8                | 4         | 5            | 5      | 3.54 |