

LED Temporary High Bay Fixture

120V: 100 Watt and 150 Watt

Features

- Up to 75% Energy savings over HID
- Weighs less than 6 lbs
- Vibration, shock, and impact resistant
- Corrosion resistant heavy-duty safety cage
- 5 foot power cord; Type SJTW300V
- Includes safety cable
- 5A resettable fuse
- Ambient operating temperature: -22°F to 140°F
- Self-locking hook/Carry handle
- Advanced thermal management with aluminum heatsink
- Receptacles in upper portion of fixture enables fixtures to be linked (100W, max. 6 fixtures; 150W, max. 4 fixtures) with anti-pull metal buckle to ensure strong connection**
- UL 94v0 rating

Applications

Suitable for use in the following areas:

- New building construction or renovation
- Any location where temporary lighting is required



Catalog Number	UPC	Ship Case	Weight Case	Watts	Lumens	CCT	Input Voltage	HID Equivalent*
17100LEDP2	03179	4	27	100W	11,000	5000K	120V	320 TO 400W
17150LEDP2	03180	4	30	150W	16,500	5000K	120V	400 TO 600W

*HID equivalent may vary dependent on application and required illuminance.

**Receptacle can only be used for linking temporary lights. Do not connect any other devices to the receptacle as this can damage the unit and create an unsafe condition.