

Rigid Couplings

Tubular Threaded Type - Aluminum

Features

- Rigid aluminum couplings are available from 1/2" thru 4"
- Manufactured from 6063 Aluminum Alloy for lightweight and corrosion resistant protection
- NPSM threads
- UL listed, UL6 / ANSI C80.5

Application


- For use with aluminum rigid conduit or elbows in a harsh or clean environment, such as waste-water treatment, food processing, oil refineries, paper mills, and power plants

Standard Material

- 6063 aluminum alloy



UL listed UL 6 and ANSI C80.5



Catalog Number	UPC	Size	Outside Diameter	Threads Per Inch	Ship Case	Weight/ Case	Inches	
							A	B
51AL	87230	1/2"	1.08"	14	100	6	1.08	1.67
52AL	87231	3/4"	1.33"	14	50	5	1.33	1.69
53AL	87232	1"	1.56"	11-1/2	30	4	1.56	1.97
54AL	87233	1-1/4"	1.95"	11-1/2	25	5	1.95	2.07
55AL	87234	1-1/2"	2.22"	11-1/2	25	6	2.22	2.11
56AL	87235	2"	2.75"	11-1/2	20	7	2.75	2.14
57AL	87236	2-1/2"	3.28"	8	12	7	3.28	3.24
58AL	87237	3"	3.97"	8	8	7	3.97	3.31
59AL	87238	3-1/2"	4.44"	8	4	4	4.44	3.41
60AL	87239	4"	5.00"	8	4	5	5	3.54