

PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192

PART NUMBER:	50308	
DESCRIPTION:	12/3 Bus Drop Cable	
CONSTRUCTION:	This cable consists of three bare copper insulated conductors and three bare copper	
	grounds cabled and an overall jacket.	
APPROVALS:	UL Misc. Wire Bus Drop Cable	

12 AWG Bare Copper

16 AWG Bare Copper

19/.0185" PVC 0.031" Nom. 0.151" Nom.

19/.0117" 3 + 3 3.00" Nom. Polypropylene Paper Tissue PVC 0.047" Nom. 0.420" Nom. 149.0 Lbs/1M' Nom.

Construction Parameters:

Conductor		
Stranding		
Insulation Material		
Insulation Thickness		
Insulated Conductor Diameter		
Ground		
Ground Stranding		
Number of Insulated Conductors + Bare Grounds		
Lay Length		
Filler Type		
Separator		
Jacket Material		
Jacket Thickness		
Overall Cable Diameter		
Approximate Cable Weight		

Electrical Properties:

Electrical i roperties.	
Temperature Rating Rated Voltage DC Resistance per Conductor @ 20 ⁰ C Ampacity	60 ^o C 600 V 1.62 Ohms/1M' Nom. Per NEC Table 310.16 and Adjustment Factors per Table 310.15(B)(2)(a)
Insulation Colors Jacket Color	Conductors: Black White Red Grounds: Bare copper Gray
Legend (Indent Print)	SOUTHWIRE® ROYAL® 🛛 🖆 🖆 E357438 12-3 BUS DROP CABLE TW INS. 600V (UL) 60C DRY 60C WET OUTDOOR
Ink Jet Print	XX/XX/XX (MONTH/DAY/YEAR) HH:MM (HOUR/MINUTE)
This product complies with European Directive 2011/65/EU (RoHS-2)	

This product complies with European Directive 2011/b5/EU (ROHS-2) The customer will accept all mil lengths and +/- 10 percent of total order requested.

Material is not returnable and purchase order is non-cancelable after production has been started or special materials have been ordered.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire's or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire. Any information contained herein shall not be disclosed to any party without written consent of Southwire.

Specification Issue Date: January 8, 2014