



Southwire®

PRODUCT SPECIFICATION

CATALOG NUMBER: See table below
DESCRIPTION: 16/2 w/gnd SPT-3 replacement power supply cord
APPROVALS: UL/CUL Listed

CONSTRUCTION PARAMETERS:

Conductor: 16 AWG, 26/30 bare copper
Conductor O.D. (nom): 0.059"
Ground conductor O.D. (nom): 0.089"
Insulation material: PVC
Insulation color: Gray
Overall cable dimensions (nom): 0.181 x 0.413"

Cord length: See table below
Attachment plug configuration: NEMA 5-15P, see table below
Plug material: PVC
Plug color: Gray
Open end configuration (nom): 1.5" separation, 0.5" strip

ELECTRICAL PROPERTIES:

Temperature rating: -20 to +60 °C
Nominal operating voltage: 125 VAC
Maximum operating current: 13 A
Maximum operating wattage: 1625 W



CATALOG NUMBERS

Catalog number	Cord length	Plug configuration	Case qty	UPC
97238809	3 ft	Right angle	25	0 29892 09723 3
97248809	4 ft		25	0 29892 09724 0
97268809	6 ft		25	0 29892 09726 4
97338809	3 ft	Straight	25	0 29892 09733 2
97348809	4 ft		25	0 29892 09734 9
97368809	6 ft		25	0 29892 09736 3

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part.

We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is the proprietary intellectual property of Southwire Company, LLC. Any information contained herein shall not be disclosed to any party without the written consent of Southwire Company, LLC.