



PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive
Waukegan, IL 60085
Toll-Free (800) 323-9355
Fax: (847) 689-1192

PART NUMBER: 60126
DESCRIPTION: 16/2 STRANDED TYPE SPT-2
CONSTRUCTION: This cable consists of two bare copper conductors laid flat with integral insulation and jacket.
APPROVALS: UL Standard 62, CSA 22.2 No. 49, NEC Article 400.
APPLICATION: 300V Flexible Cable

Construction Parameters:

Conductor	16 AWG Bare Copper
Stranding	26/30
Insulation Material	PVC
Insulation Thickness	0.048" Nom.
Insulated Conductor Diameter	0.155" x 0.303" Nom.
Number of Conductors	2
Approximate Cable Weight	36.0 Lbs/1M' Nom.
Flame Rating	UL/CSA Horizontal Flame Test

Electrical Properties:

Temperature Rating	-20°C to 60°C
Operating Voltage	300 V RMS Max.
DC Resistance per Conductor @ 20°C	3.46 Ohms/1M' Nom.

Insulation/Jacket Colors	Black, Brown, White (Other colors available for minimum order - consult factory)
Legend (Indent Print)	16 AWG (1.31mm ²) 2/C E46194 (UL) SPT-2 60C 300V -- 156205 CSA SPT-2 60C 300V FT1

This product complies with European Directive 2011/65/EU (RoHS-2)

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire. Any information contained herein shall not be disclosed to any party without written consent of Southwire.

Specification Issue Date: August 7, 2014