

# Rigid/Swivel Optional Spouts

**TECK<sup>®</sup>**  
COMMERCIAL

**DELTA<sup>®</sup>**


## SPECIFYING PROCEDURE FOR OPTIONAL RIGID/SWIVEL SPOUTS:

1. Select **BASE PRODUCT** with **Standard Gooseneck Spout**, and with spout outlet and handles required.
2. Select **Optional Rigid/Swivel Spout R or LS-R** ("ADD-ON" Suffix Number)
3. Attach "ADD-ON" Suffix Number Spout selected to Base Product as a dash Suffix. (-R) or (-LS-R)


Note: Refer to BASE PRODUCT specification sheet for suffix availability.

- EG: 1.** (1) Base Product selected: **23C644**  
 (2) Optional Spout selected: **LS-R7**  
 (120° Limited swing, 9" bend gooseneck selected)  
 (3) End Product Number to Specify: **23C644-LS-R7**
- EG: 2.** (1) Base Product selected: **27C4924**  
 (2) Optional Spout selected: **R7**  
 (9" gooseneck spout selected)  
 (3) End Product Number to Specify: **27C4924-R7**


**GROUP NO. 1**  
Regular Gooseneck



**GROUP NO. 2**  
Smooth End-Flow Control in Base of Gooseneck Spout (Available on #7 or #8 outlets ONLY)



**GROUP NO. 3**  
Double Joint



SPOUT GROUP NUMBER	Rigid Swivel "ADD-ON" SUFFIX NUMBER	LIMITED SWING "ADD-ON" SUFFIX NUMBER	SPOUT DESCRIPTION	"A"		"C"		"L"	
				mm	in.	mm	in.	mm	in.
<b>1</b>	<b>R2</b>	<b>LS-R2</b>	Gooseneck Spout	114	4.5	104	4.1	170	6.7
	<b>R4</b>	<b>LS-R4</b>	Gooseneck Spout	152	6	124	4.9	146	5.8
	<b>R5</b>	<b>LS-R5</b>	Gooseneck Spout	152	6	124	4.9	188	7.4
	<b>R6</b>	<b>LS-R6</b>	Gooseneck Spout	152	6	124	4.9	229	9
	<b>R7</b>	<b>LS-R7</b>	Gooseneck Spout	229	9	163	6.4	170	6.7
<b>2</b>	<b>R35</b>	<b>LS-R35</b>	Gooseneck Spout	152	6	124	4.9	94	3.7
	<b>R2</b>	---	GN Spout w/Flow Cont.	114	4.5	97	3.8	178	7
	<b>R4</b>	---	GN Spout w/Flow Cont.	152	6	117	4.6	152	6
	<b>R5</b>	---	GN Spout w/Flow Cont.	152	6	117	4.6	196	7.7
	<b>R6</b>	---	GN Spout w/Flow Cont.	152	6	117	4.6	236	9.3
<b>3</b>	<b>R7</b>	---	GN Spout w/Flow Cont.	229	9	155	6.1	178	7
	<b>R35</b>	---	GN Spout w/Flow Cont.	152	6	117	4.6	102	4
<b>3</b>	<b>R17</b>	---	Double Joint Spout	359	14.1	38	1.5	218	8.6

ALL gooseneck spouts are made from .09 heavy wall seamless brass pipe. Swing spout portion of R17 is brass tubular wall spout.

Note: Measurements may vary ± 6mm (0.25")

Refer to [www.specselect.com](http://www.specselect.com) for individual models.