

Lavatory Faucets

Widespread with CER-TECK® ceramic structures

Model No: 23C335

COMPLIES WITH:

CSA certified

- Complies to ASME A112.18.1/CSA B125.1
- Verified compliant with 0.25% weighted average Pb content regulations
- Ė.

Handles No. 2, 3, 4, and 5 Indicates compliance to ICC/ANSI A117.1

- Outlet options 2, 3, 4 and 7 are EPA WaterSense listed
- (Contact Delta Representative for State and/or Local Approvals)







NOTES:

Product Variations(23C3) - NOTE: For Best Delivery, order CER-TECK®

SPECIFICATION:


- Two handle widespread lavatory faucet
- 152 to 305mm (6" to 12") adjustable centers
- Polished chrome plated finish trim
- CAST BRASS bodies
- 4 1/2" CAST BRASS spout or 3/8" IPS BRASS PIPE Rigid/Swivel Gooseneck Spout
- Metal hold-down package
- Color indexed metal handles with vandal resistant screws
- CER-TECK® 1/4 turn ceramic structures
- Outlet#: 3 Vandal Resistant 1.5 gpm (5.7L/min) Flow Control Aerator
- Handle#: 5 152 mm (6") Wrist Blade Handles-ADA Compliant- Sanitary Hoods-Metal-Color indexed-Vandal resistant screws
- Cast Spout,Less Pop-up (No Pop-up Hole)

OPERATION:

Not Available

(Dimensional drawing on following page)





Delta reserves the right (1) to make changes to specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference. Measurement may vary plus or minus 6mm(0.25"). Mounting locations are suggested only. Check with local codes for requirements in your area. This spec was produced May 24, 2017.