




# SPECIFICATION




## No. 60-2 for 3/4" Pitch Double Strand Chain




**TYPE ATL**



**TYPE BTL 1**



**TYPE BTL 2**



**TYPE B**

| TAPER-LOCK - DOUBLE STRAND |            |                 |               |               |            |            |         |      |
|----------------------------|------------|-----------------|---------------|---------------|------------|------------|---------|------|
| No. Teeth                  | Spkt. O.D. | Description ★   | Part No.      | Wt. w/o Bush. | C Hub Dia. | Bore Range |         | B    |
|                            |            |                 |               |               |            | Min.       | Max.    |      |
| 13                         | 3.493      | D60BTL13H-1215• | <b>101061</b> | 1.4           | 2.46       | 1/2        | 1-1/4   | 1.50 |
| 14                         | 3.736      | D60BTL14H-1215• | <b>101062</b> | 1.7           | 2.49       |            | 1-1/4   |      |
| 14T                        | 3.736      | D60BTL14H-1615• | <b>101086</b> | 1.7           | 2.74       |            | 1-11/16 |      |
| 15                         | 3.978      | D60BTL15H-1615• | <b>101063</b> | 1.8           | 2.47       | 1/2        | 1-11/16 | 1.50 |
| 16                         | 4.220      | D60BTL16H-1615• | <b>101064</b> | 2.4           | 2.97       |            | 1-11/16 |      |
| 17                         | 4.462      | D60BTL17H-1615  | <b>101065</b> | 2.6           | 3.25       |            | 1-11/16 |      |
| 18                         | 4.703      | D60ATL18H-2012  | <b>101066</b> | 2.8           | ...        | 1/2        | 2-1/8   | 1.25 |
| 19                         | 4.945      | D60ATL19H-2012  | <b>101067</b> | 3.1           | ...        |            | 2-1/8   |      |
| 20                         | 5.186      | D60BTL20H-2517• | <b>101068</b> | 3.3           | 3.95       | 1/2        | 2-11/16 | 1.75 |
| 21                         | 5.426      | D60BTL21H-2517• | <b>101069</b> | 4.3           | 4.06       |            | 2-11/16 |      |
| 22                         | 5.666      | D60BTL22H-2517  | <b>104848</b> | 5.5           | 4.25       |            | 2-11/16 |      |
| 23                         | 5.907      | D60BTL23H-2517  | <b>104849</b> | 6.1           | 4.25       |            | 2-11/16 |      |
| 24                         | 6.147      | D60BTL24H-2517  | <b>104850</b> | 7.2           | 4.25       | 1/2        | 2-11/16 | 1.75 |
| 25                         | 6.387      | D60BTL25H-2517  | <b>101070</b> | 8.0           |            |            |         |      |
| 26                         | 6.627      | D60BTL26-2517   | <b>104914</b> | 10.2          |            |            |         |      |
| 27                         | 6.867      | D60BTL27-2517   | <b>101083</b> | 10.8          |            |            |         |      |
| 28                         | 7.106      | D60BTL28-2517   | <b>104851</b> | 11.9          |            |            |         |      |
| 29                         | 7.346      | D60BTL29-2517   | <b>101084</b> | 12.7          |            |            |         |      |
| 30                         | 7.586      | D60BTL30-2517   | <b>101071</b> | 13.4          |            |            |         |      |
| 32                         | 8.065      | D60BTL32-2517   | <b>104852</b> | 15            |            |            |         |      |
| 35                         | 8.783      | D60BTL35-2517   | <b>104853</b> | 17            |            |            |         |      |
| 36                         | 9.023      | D60BTL36-2517   | <b>101072</b> | 18            |            |            |         |      |
| 40                         | 9.980      | D60BTL40-2517   | <b>104854</b> | 23            | 5.25       | 7/8        | 3-1/4   | 2.0  |
| 42                         | 10.458     | D60BTL42-2517   | <b>101073</b> | 26            |            |            |         |      |
| 45                         | 11.176     | D60BTL45-2517   | <b>101074</b> | 30            |            |            |         |      |
| 48                         | 11.893     | D60BTL48-2517   | <b>104855</b> | 36            |            |            |         |      |
| 52                         | 12.849     | D60CTL52-2517   | <b>101075</b> | 41            | 5.25       | 7/8        | 3-1/4   | 2.0  |
| 60                         | 14.761     | D60BTL60-2517   | <b>101076</b> | 33            |            |            |         |      |
| 68                         | 16.673     | D60CTL68-2517   | <b>101077</b> | 37            |            |            |         |      |
| 70                         | 17.150     | D60BTL70-3020   | <b>104857</b> | 77            | 5.25       | 7/8        | 3-1/4   | 2.0  |
| 72                         | 17.628     | D60BTL72-3020   | <b>104858</b> | 83            |            |            |         |      |
| 76                         | 18.584     | D60BTL76-3020   | <b>101078</b> | 42            |            |            |         |      |

★ "H" suffix indicates Hardened Teeth.

• BTL1

| REBORABLE-TYPE B |            |               |               |     |       |       |      |            |
|------------------|------------|---------------|---------------|-----|-------|-------|------|------------|
| No. Teeth        | Spkt. O.D. | Description ★ | Part No.      | Wt. | Bore  |       | B    | C Hub Dia. |
|                  |            |               |               |     | Stock | Max   |      |            |
| 13               | 3.493      | D60B13H       | <b>105201</b> | 2.6 | 3/4   | 1-1/2 | 2.13 | 2.25       |
| 14               | 3.736      | D60B14H       | <b>105202</b> | 3.2 | 3/4   | 1-3/4 | 2.13 | 2.50       |
| 15               | 3.978      | D60B15H       | <b>105203</b> | 3.8 | 3/4   | 1-7/8 | 2.13 | 2.75       |
| 16               | 4.220      | D60B16H       | <b>105204</b> | 4.5 | 3/4   | 2     | 2.13 | 3.00       |
| 17               | 4.462      | D60B17H       | <b>105205</b> | 5.3 | 3/4   | 2-1/4 | 2.13 | 3.22       |
| 18               | 4.703      | D60B18H       | <b>105206</b> | 6.5 | 1     | 2-3/8 | 2.13 | 3.44       |
| 19               | 4.945      | D60B19H       | <b>105207</b> | 7.2 | 1     | 2-1/2 | 2.13 | 3.69       |
| 20               | 5.186      | D60B20H       | <b>105208</b> | 7.7 | 1     | 2-1/2 | 2.13 | 3.75       |
| 21               | 5.426      | D60B21H       | <b>105209</b> | 9.0 | 1     | 2-3/4 | 2.13 | 4.13       |

★ "H" suffix indicates Hardened Teeth.

FEATURES/BENEFITS  
PAGE PT12-2

SELECTION  
PAGES PT12-28 - PT12-39

RELATED PRODUCTS  
PAGES PT12-40 - PT12-42

ENGINEERING/TECHNICAL  
PAGES PT12-43 -PT12-46