

# **BALDOR® • RELIANCE**

## **Product Information Packet**

**009024**

**3-1/2 RIBBED RIGID CPLG**

| Specs                    |               |  |  |
|--------------------------|---------------|--|--|
| ATEX Certified:          | NO            |  |  |
| Bore Tolerance Standard: | CUSTOM        |  |  |
| Product Family:          | Rigid         |  |  |
| Shaft Attachment:        | FINISHED BORE |  |  |
| Shaft Spacing:           | CLOSE-COUPLED |  |  |
| Torsional Rigidity:      | RIGID         |  |  |
| Coupling Style:          | RIBBED RIGID  |  |  |

| Parts List  |                                         |          |
|-------------|-----------------------------------------|----------|
| Part Number | Description                             | Quantity |
| 009040      | 3-7/16 RIB SHIM                         | 2.000 EA |
| 009071      | 3-7/16 RIB CPL CASTING                  | 2.000 EA |
| 407097      | 7/8 9NC REG HEX NUT#2                   | 6.000 EA |
| 411511      | 7/8-9X3 HHCS GR5                        | 6.000 EA |
| 440094      | 13-1/2X9X9                              | 1.000 EA |
| 443157      | 7/8 X 7/8 X 13-3/16 KEY                 | 1.000 EA |
| 499616      | RIBBED COUPLING MANUAL                  | 1.000 EA |
| DODGE2      | DODGE LABEL 2                           | 1.000 EA |
| 441300      | LIFT STICKER WEIGHT BETWEEN 55 & 100LBS | 1.000 EA |