




SPECIFICATION




No. 50-2 for 5/8" Pitch Double Strand Chain




TYPE ATL



TYPE BTL



TYPE CTL



TYPE B

TAPER-LOCK								
No. Teeth	Spkt. O.D.	Description ★	Part No.	Wt. w/o Bush.	C Hub Dia.	Bore Range		B
						Min.	Max.	
14	3.113	D50ATL14H-1008	101031	.9		1/2	1.0	.88
15	3.315	D50ATL15H-1210	101032	1.0		1/2	1-1/4	1.0
16	3.517	D50ATL16H-1210	101033	1.1				
17	3.718	D50ATL17H-1610	101034	1.1		1/2	1-11/16	1.0
18	3.919	D50ATL18H-1610	101035	1.4				
19	4.121	D50ATL19H-1610	101036	1.7				
20	4.321	D50BTL20H-2012	101037	1.9	3.56	1/2	1-11/16	1.25
21	4.522	D50BTL21H-2012	101038	2.0				
22	4.722	D50BTL22H-2012	104834	2.5				
23	4.923	D50BTL23H-2012	104835	3.0				
24	5.123	D50BTL24H-2012	104836	3.5				
25	5.323	D50BTL25H-2012	101039	4.0	4.25	1/2	2-11/16	1.75
26	5.523	D50BTL26-2012	104837	4.7				
28	5.922	D50BTL28-2012	104838	6.3				
30	6.321	D50BTL30-2517	101040	7.8				
32	6.721	D50BTL32-2517	104839	8.4				
35	7.319	D50BTL35-2517	104840	9.2				
36	7.519	D50BTL36-2517	101041	10.0				
40	8.316	D50BTL40-2517	104841	12.7				
42	8.715	D50BTL42-2517	101042	14.2				
45	9.313	D50BTL45-2517	104842	16.1				
48	9.911	D50BTL48-2517	101043	18.7				
52	10.708	D50BTL52-2517	101044	22.5				
54	11.106	D50BTL54-2517	104843	25.2				
60	12.301	D50BTL60-2517	101045	36.5				
68	13.894	D50BTL68-2517	101046	39.5				
70	14.292	D50BTL70-2517	104844	42.7				
72	14.329	D50BTL72-2517	104845	45.0				
76	15.486	D50BTL76-2517	101047	49.5				
80	16.283	D50BTL80-2517	104846	51.0				
84	17.079	D50BTL84-2517	101048	52				
95	19.268	D50CTL95-2517	101049	70				
102	20.661	D50CTL102-2517	101050	75				

★ "H" suffix indicates Hardened Teeth.

REBORABLE—TYPE B								
No. of Teeth	Spkt. O.D.	Description ★	Part No.	Wt.	Bore		B	C Hub Dia.
					Stock	Max.		
13	2.911	D50B13H	105932	1.5	5/8	1-5/16	1.75	1.88
14	3.113	D50B14H	105193	1.8	5/8	1-3/8	1.75	2.09
15	3.315	D50B15H	105194	2.0	5/8	1-1/2	1.75	2.28
16	3.567	D50B16H	105195	2.4	5/8	1-5/8	1.75	2.50
17	3.718	D50B17H	105196	2.9	5/8	1-7/8	1.75	2.69
18	3.919	D50B18H	105197	3.3	5/8	1-15/16	1.75	2.88
19	4.121	D50B19H	105198	3.7	5/8	2-1/8	1.75	3.09
20	4.321	D50B20H	105199	4.4	5/8	2.25	1.75	3.28
21	4.522	D50B21H	105200	4.8	3/4	2-3/8	1.75	3.50
26	5.523	D50B26	105222	7.5	15/16	2-1/2	1.88	3.75

★ "H" suffix indicates Hardened Teeth.

FEATURES/BENEFITS
PAGE PT12-2

SELECTION
PAGES PT12-28 - PT12-39

RELATED PRODUCTS
PAGES PT12-40 - PT12-42

ENGINEERING/TECHNICAL
PAGES PT12-43 -PT12-46