




Standard Construction Features

Belt Type: Synchronous

Core Material: Oil & Heat Resistant (chloroprene)

Cord/Tensile: Fiberglass

Jacket: Nylon



Belt Section Dimensions


Tooth Type	Pitch (mm)	h_s (mm)	h_t (mm)
HTD	20	13.200	8.400

Belt Dimensions

Pitch Length (mm)	No. Teeth	Width (mm)
6400.00 + 0.000 - 0.000	320	170.000 + 2.400 - 3.200

Measuring Information

Y (mm)	T (N)	No. Teeth	O.D. (mm)	Pitch Circum. (mm)	Radial Runout (mm)	Axial Runout (mm)	PLD 2a (mm)
2800.00 + 0.000 + 0.000	10729	40	250.33	800.00	0.0005	0.0010	4.318



The length shall be measured by placing the belts on two pulleys of equal diameters that have been grooved in accordance with standard specifications and rotated at least three complete turns with the specified tension so that each strand receives half the total tension. The length will be that length obtained by adding the Pitch Circumference of one pulley to twice the center distance (dimension 'Y').



DesignView™ Belt Information Sheet

Created 30 Jun 2017 by Gates

Created for

Gates: PowerGrip GT2 - 20M

Gates Product Number

9293-0728

Customer Part Number

6400-20M-170