


### Standard Construction Features

Belt Type: Banded  
 Core Material: General Purpose (diene)  
 Cord/Tensile: Polyester  
 BandPly 1: Oil & Heat Resistant Standard  
 BandPly 2: Oil & Heat Resistant Standard



### Belt Section



Cross Section	Datum Length (in)	TW (in)	TH (in)
BB	117.80 $\pm 0.80$	21/32	17/32

### Measuring Information

\* T (lb) is per belt/rib/strand

Y (in)	T* (lb)	G min (in)	W (in)	Angle (°)	O.D. (in)	O.C. (in)	Max Ride (in)	S (in)
50.449 $\pm 0.400$	65	0.55	0.637	34	5.730	16.902	.03	0.75

Reference RMA IP-21 1991 for the industry standard governing this belt.



The length shall be measured by placing the belts on two sheaves of equal diameters that have been grooved in accordance with standard specifications and rotated at least three complete turns with the specified tension so that each strand receives half the total tension. The length will be that length obtained by adding the Reference Circumference of one sheave at dimension 'W' to twice the center distance (dimension 'Y').



**DesignView™**  
 Version 1.0 -  
 Belt Information Sheet

Created 21 Jun 2017 by Gates

Created for  
**Hi-Power II - BB**

Gates Product Number  
**9053-0116**

Customer Part Number  
**BB116**