



APPROVAL

- NOTES:
1. APPROX WEIGHT: 1.07 LBS.
 2. BELT PITCH: 8M
 3. NUMBER OF TEETH: 32
 4. PITCH DIAMETER: 3.208 REF
 5. STATIC BALANCED.
 6. DRILL, TAP AND TAPER BORE FOR A "1210" TL BUSHING.
 7. ASSEMBLE WITH (2) FLANGES (PN 117936.)
 8. MATERIAL: CAST IRON.

THE MATERIALS AND INFORMATION, INCLUDING THE PRINCIPALS OF DESIGN PRESENTED, ARE THE EXCLUSIVE PROPERTY OF THE GATES RUBBER COMPANY AND ARE TO BE CONSIDERED AS CONFIDENTIAL INFORMATION. ACCORDINGLY, THIS INFORMATION IS SUBMITTED TO YOU WITH THE ASSEMBLY TAP. IT IS NOT TO BE REPRODUCED, COPIED, OR LOANED, IN PART OR IN WHOLE, NOR IS THE INFORMATION TO BE RELATED TO ANY OTHER INDIVIDUAL OR COMPANY. ACCEPTANCE OF THIS DRAWING WILL BE CONSTRUED AS AN AGREEMENT TO THE ABOVE.

THIS DRAWING IS A STOCK POWER TRANSMISSION COMPONENT. DETAILS SHOWN WHICH DO NOT AFFECT DRIVE FUNCTION MAY BE CHANGED WITHOUT ANY NOTIFICATION.

ORDER NO.: _____
CUSTOMER ORDER NO.: _____

PRODUCT: HT SPROCKET
PART: P32-8M-12-1210 CI

APPROVED BY: _____
DATE: _____

DIST. DAY

Gates
GATES CORPORATION
DENVER, COLORADO

DR. BY: _____
CK. BY: _____
APPD. BY: GEB

DRAWING NO. 77081232