

APPROVAL


- NOTES:
1. BELT PITCH: 14M
 2. NUMBER OF TEETH: 154
 3. PITCH DIAMETER: 27.019 REF
 4. DRILL, TAP AND TAPER BORE FOR A "3525" TL.)
 5. APPROX. WEIGHT: 100.19 LBS.
 6. MATERIAL: CAST IRON.
 7. STATIC BALANCED.

THE MATERIALS AND INFORMATION, INCLUDING THE PRINCIPALS OF DESIGN PRESENTED, ARE THE EXCLUSIVE PROPERTY OF THE GATES RUBBER COMPANY AND ARE TO BE CONSIDERED AS CONFIDENTIAL INFORMATION. ACCORDINGLY, THIS INFORMATION IS SUBMITTED TO YOU WITH THE AGREEMENT THAT IT IS NOT TO BE REPRODUCED, COPIED, OR LOANED, IN PART OR IN WHOLE, NOR IS THE INFORMATION TO BE RELAYED TO ANY OTHER INDIVIDUAL OR COMPANY. ACCEPTANCE OF THIS DRAWING WILL BE CONSTRUED AS AN AGREEMENT TO THE ABOVE.

THIS DRAWING IS A STOCK POWER TRANSMISSION COMPONENT. DETAILS SHOWN WHICH DO NOT AFFECT DRIVE FUNCTION MAY BE CHANGED WITHOUT ANY NOTIFICATION.

ORDER NO. :	PRODUCT	APPROVED BY	DIST.
CUSTOMER ORDER NO. :	PART	DATE	DAV

MTD POLYCHAIN SPROCKET
MTO 14MX-154S-37-3525 CI

 **GATES CORPORATION**
DENVER, COLORADO

DR. BY MW DATE 01/09/2008
CK. BY
APPD. BY PYM

DRAWING NO.

77193154 A