




Standard Construction Features

Belt Type: Synchronous

Core Material: Oil & Heat Resistant (chloroprene)

Cord/Tensile: Fiberglass

Jacket: Nylon



Belt Section Dimensions

| Tooth Type | Pitch (mm) | h_s (mm) | h_t (mm) |
|------------|------------|------------|------------|
| GT | 8.000 | 8.180 | 3.480 |

Belt Dimensions

| Pitch Length (mm) | No. Teeth | Width (mm) |
|-------------------------------|-----------|-------------------------------|
| 880.00 ± 0.660 - 0.660 | 110 | 85.000 ± 0.000 - 0.000 |

Measuring Information

| Y (mm) | T (N) | No. Teeth | O.D. (mm) | Pitch Circum. (mm) | Radial Runout (mm) | Axial Runout (mm) | PLD 2a (mm) |
|-----------------------------------|-------|-----------|-----------|--------------------|--------------------|-------------------|-------------|
| 344.00 ± 0.330 ± 0.330 | 0 | 24 | 59.74 | 192.00 | 0.0005 | 0.0030 | 1.372 |



The length shall be measured by placing the belts on two pulleys of equal diameters that have been grooved in accordance with standard specifications and rotated at least three complete turns with the specified tension so that each strand receives half the total tension. The length will be that length obtained by adding the Pitch Circumference of one pulley to twice the center distance (dimension 'Y').



DesignView™ Belt Information Sheet

Created 28 Jun 2017 by Gates

Created for

PowerGrip Twin Power - 8MGT2

Gates Product Number

9232-0028

Customer Part Number

TP880-8MGT-85