



CERTIFIED

SOCKET HEAD CAP SCREWS
FOR BUSHING INSTALLATION

DATE	REV	DATE	APP'D	REVISION

TOOTH TYPE: GT

BELT PITCH: 14M

PITCH DIA: 9.825

NO. OF TEETH: 56

MATERIAL: GRAY IRON

FINISH: 250 ✓

COATINGS: ANTI-RUST

THE MATERIALS AND INFORMATION, INCLUDING THE PRINCIPALS OF DESIGN PRESENTED, ARE THE EXCLUSIVE PROPERTY OF THE GATES RUBBER COMPANY AND ARE TO BE CONSIDERED AS CONFIDENTIAL INFORMATION. ACCORDINGLY, THIS INFORMATION IS SUBMITTED TO YOU WITH THE AGREEMENT THAT IT IS NOT TO BE REPRODUCED, COPIED, OR LOANED, IN PART OR IN WHOLE, NOR IS THE INFORMATION TO BE RELAYED TO ANY OTHER INDIVIDUAL OR COMPANY. ACCEPTANCE OF THIS DRAWING WILL BE CONSTRUED AS AN AGREEMENT TO THE ABOVE.

THIS DRAWING IS A STOCK POWER TRANSMISSION COMPONENT. DETAILS SHOWN WHICH DO NOT AFFECT DRIVE FUNCTION MAY BE CHANGED WITHOUT ANY NOTIFICATION.

CUSTOMER NAME:

CUSTOMER DWG NO.:



THE GATES RUBBER CO.
DENVER, COLORADO

PART DESCRIPTION: P56-14MGT-85 3535

GATES PART NUMBER: 77118056

APPROVED BY _____

DATE _____

DR. BY _____ DATE _____

CK. BY _____

APPD. BY _____

REF. QUOTE NO.

DRAWING NO.

77118056