

FLUSH TYPE



EXCEEDS 72 HR SALT SPRAY.

DRIVE TYPE

Flush drive type fittings have an advantage of not needing a threaded hole, therefore decreasing the cost of installation. These grease fittings can be serviced by a variety of hand oilers including those found on page 131. The midget flush type coupler H84205, found on page 123, is recommended for the H1877.

H1877

Straight Flush Drive Type
≈ 1/8" Drill Size
Smooth Shank




1877
700397

CADMIUM
+ AVAILABLE IN MONEL®

H3036Z3


Straight Flush Drive Type
≈ 3/16" Drill Size
Serrated Shank



3036

H1814Z3


Straight Flush Drive Type
≈ 5/16" Drill Size
Smooth Shank



1814

H369604


Straight Flush Drive Type
≈ 1/4" Drill Size
Serrated Shank



369604

H1885Z3

Straight Flush Drive Type
≈ 1/4" Drill Size
Smooth Shank



1885
700502

PLEASE NOTE

HOLE SIZES PROVIDED
ARE FOR REFERENCE.
G.L. HUYETT RECOMMENDS
TESTING TO ENSURE
RELIABILITY IN THE FIELD.

Item #	Drill Diameter	Shank Type	Overall Length (A)	Shank Length (B)	Min. Thread Length (C)	Thread Diameter (F)	Shoulder Diameter (H)
H1877	≈ 1/8" Drill	Smooth Shank	.17"	.13"	—	—	5/32"
H3036Z3	≈ 3/16" Drill	Serrated Shank	.37"	.31"	—	—	1/4"
H1814Z3	≈ 5/16" Drill	Smooth Shank	.33"	.28"	—	—	3/8"
H369604	≈ 1/4" Drill	Serrated Shank	.34"	.33"	—	—	5/16"
H1885Z3	≈ 1/4" Drill	Smooth Shank	.28"	.23"	—	—	5/16"