

HEAVY DUTY

MANUFACTURER CROSS-REFERENCE

INDEX PAGE 236.

Standard Locknut	TW	
Whittet-Higgins	WH	

WH

Bearing Bore Nominal (N) Decimal	MM	LOCKWASHER DIMENSIONS: Free Outside Dia. +0/-1/16"(OD)	Inside Dia. (ID) Min./Max.	Thickness (T) Min./Max.	Face Dia. (Dc) Min./Max.	Number of Tangs	WEIGHT Lbs. per 100 Pieces	MATERIAL: Spring Steel	Mating Locknut
WH-00	.3937	10	57/64	.406/.421	.038/.046	.625/.640	9	0.3750		NH-00
-01	.4724	12	1-1/32	.484/.499		.719/.734		0.5000		-01
-02	.5906	15	1-5/32	.601/.616	.053/.063	.813/.827	11	0.9375		-02
-03	.6693	17	1-11/32	.679/.694		.938/.953		1.2500		-03
-04	.7874	20	1-9/16	.801/.816		1.125/1.140		1.7190		-04
-05	.9843	25	1-45/64	.989/1.009	.057/.067	1.281/1.296	13	2.1429		-05
-06	1.1811	30	1-61/64	1.193/1.213		1.500/1.515		2.1875		-06
-065	1.3125	33-1/3	2-15/64	1.333/1.353		1.813/1.827	15	3.3929		-065
-07	1.3780	35	2-1/4	1.396/1.416		1.813/1.827		3.2143		-07
-08	1.5748	40	2-31/64	1.583/1.603	.067/.077	2.000/2.030		4.4440		-08
-09	1.7717	45	2-23/32	1.792/1.817		2.281/2.311	17	5.2083		-09
-10	1.9685	50	2-59/64	1.992/2.017		2.438/2.468		5.3570		-10
-11	2.1654	55	3-3/32	2.182/2.207		2.656/2.686		5.7143		-11
-12	2.3622	60	3-21/64	2.400/2.425	.077/.087	2.844/2.874		6.9640		-12
-13	2.5591	65	3-9/16	2.588/2.613		3.063/3.093	19	8.2143		-13
-14	2.7559	70	3-13/16	2.791/2.816		3.313/3.343		9.1667		-14
-15	2.9528	75	4-3/64	2.973/3.003	.089/.101	3.563/3.593		12.1875		-15
-16	3.1496	80	4-25/64	3.177/3.207		3.844/3.874		15.6250		-16
-17	3.3465	85	4-5/8	3.395/3.425		4.031/4.061		16.5630		-17
-18	3.5433	90	4-61/64	3.582/3.612	.118/.132	4.281/4.326		24.5830		-18
-19	3.7402	95	5-15/64	3.800/3.830		4.563/4.607		27.0830		-19
-20	3.9370	100	5-31/64	3.988/4.018		4.813/4.858		30.0000		-20
-21	4.1339	105	5-45/64	4.192/4.222		5.000/5.045		31.3889		-21
-22	4.3307	110	6	4.395/4.425	.133/.147	5.281/5.326		38.7500		-22
-24	4.7244	120	6-17/32	4.801/4.831	.157/.173	5.688/5.733		51.2500		-24
-26	5.1181	130	7-3/64	5.191/5.226		6.188/6.233		66.2500		-26
-28	5.5118	140	7-7/16	5.582/5.617		6.531/6.576		67.5000		-28
-30	5.9055	150	8-1/16	5.983/6.018	.194/.212	7.063/7.123		96.8750		-30
-32	6.2992	160	8-29/64	6.389/6.424		7.438/7.498		100.0000		-32
-34	6.6929	170	9-5/64	6.764/6.799		8.031/8.091		120.0000		-34
-36	7.0866	180	9-7/16	7.171/7.206		8.375/8.435		127.5000		-36
-38	7.4803	190	9-55/64	7.577/7.612		8.781/8.841		132.5000		-38
WH-40	7.8740	200	10-13/32	7.982/8.017		9.156/9.216		140.0000		NH-40

MATING LOCKNUT DESCRIPTIONS ON PAGE 133.

WH

AXIAL ASSEMBLY

DESCRIPTION

Heavier duty, thicker version with the key bent in the same direction as the tangs.

HOW TO IDENTIFY

1. Verify the face diameter (Dc) of the part.
2. Confirm the (ID) of the part.
3. Measure the thickness (T).
4. Find the part in the chart above.

GENERAL USE



UNCOMMON

USE WITH NH LOCKNUTS.

FOR THINNER VERSION, SEE "W" ON PAGE 141.

NH LOCKNUT Page 133

MOST SIZES AVAILABLE IMMEDIATELY • $2 LINE REQUESTED • CALL PLANT FOR QUANTITY DISCOUNTS

All manufacturer names and numbers are for identification purposes only. In no way are we implying that our parts were made by the manufacturers listed above.
Prices, materials, tolerances, and grades subject to change without notice.
© G.L. Huyett 2004