
M7 & M8

EXCEEDS 72 HR SALT SPRAY.
8,000 PSI MAX PRESSURE.


DIN 71412

G.L. Huyett offers an extensive line of metric grease fittings for a variety of applications, including 7.0 mm which is an uncommon thread type. The fine threaded M8 x 0.75 offers added thread engagement.


H2139
Straight
M7 x 1.0 Taper Thread
Standard Shank




H2140
45° Angle
M7 x 1.0 Taper Thread
Standard Shank




H2141
90° Angle
M7 x 1.0 Taper Thread
Standard Shank




H2118
Straight
M8 x 0.75 Taper Thread
Standard Shank



H2119
45° Angle
M8 x 0.75 Taper Thread
Standard Shank



H2120
90° Angle
M8 x 0.75 Taper Thread
Standard Shank



ITEM #	THREAD	ANGLE (E)	OVERALL LENGTH (A)	SHANK LENGTH (B)	MIN. THREAD LENGTH (C)	OVERALL WIDTH (D)	THREAD DIAMETER (F)	SWING CLEARANCE (G)	HEX (H)
H2139	M7 X 1.0	STRAIGHT	15.0 MM	5.5 MM	3.7 MM	□	7.0 MM	□	9.0 MM
H2140	M7 X 1.0	45□	23.5 MM	5.5 MM	3.7 MM	15.0 MM	7.0 MM	10.0 MM	9.0 MM
H2141	M7 X 1.0	90□	18.0 MM	5.5 MM	3.7 MM	17.0 MM	7.0 MM	13.0 MM	9.0 MM
H2118	M8 X 0.75	STRAIGHT	15.0 MM	5.5 MM	3.7 MM	□	8.0 MM	□	9.0 MM
H2119	M8 X 0.75	45□	23.5 MM	5.5 MM	3.7 MM	15.0 MM	8.0 MM	10.0 MM	9.0 MM
H2120	M8 X 0.75	90□	18.0 MM	5.5 MM	3.7 MM	17.0 MM	8.0 MM	13.0 MM	9.0 MM

TECHNICAL DRAWINGS ARE APPROXIMATE ACTUAL SIZE

Common Parts
Parts with this designation are in wide distribution.

Alemite®
Alemite® is a registered trademark of Alemite, LLC, Johnson City, TN, USA.

Lincoln Industrial®
Lincoln Industrial® is a registered trademark of Lincoln Industrial (USA) Corp.

John Deere®
John Deere® is a registered trademark of Deere and Company, Moline, Illinois.

All manufacturer names and numbers are for cross reference identification purposes only. In no way are we implying that our parts were made by the manufacturers listed.
Prices, materials, dimensions, tolerances, designs and grades subject to change without notice. © G.L. Huyett 2011