M5 & M6

EXCEEDS 72 HR SALT SPRAY. 8,000 PSI MAX PRESSURE.

DIN 71412

TECHNICAL DRAWINGS ARE APPROXIMATE ACTUAL SIZE

G.L. Huyett offers an extensive line of metric grease fittings for a variety of applications. 5.0 mm shanks are for use in light-duty applications. If the grease fitting you are looking for is not listed, call our Sales Team for assistance.

H2100Z3

Straight
M5 x 0.8 Taper Thread
Standard Shank



AVAILABLE IN STAINLESS

H2101Z3

45° Angle
M5 x 0.8 Taper Thread
Standard Shank



H2102Z3

90° Angle
M5 x 0.8 Taper Thread
Standard Shank



H2115Z3

Straight
M6 x 0.75 Taper Thread
Standard Shank



AVAILABLE IN STAINLESS

H2116Z3

45° Angle
M6 x 0.75 Taper Thread
Standard Shank



H2117Z3

90° Angle
M6 x 0.75 Taper Thread
Standard Shank



Item #	Thread	Angle (E)	Overall Length (A)	Shank Length (B)	Min. Thread Length (C)	Overall Width (D)	Thread Diameter (F)	Swing Clearance (G)	Hex (H)
H2100Z3	M5 x 0.8	Straight	15.0 mm	5.5 mm	3.7 mm	—	5.0 mm	—	7.0 mm
H2101Z3	M5 x 0.8	45°	23.5 mm	5.5 mm	3.7 mm	15.0 mm	5.0 mm	10.0 mm	9.0 mm
H2102Z3	M5 x 0.8	90°	18.0 mm	5.5 mm	3.7 mm	17.0 mm	5.0 mm	13.0 mm	9.0 mm
H2115Z3	M6 x 0.75	Straight	15.0 mm	5.5 mm	3.7 mm	—	6.0 mm	—	7.0 mm
H2116Z3	M6 x 0.75	45°	23.5 mm	5.5 mm	3.7 mm	15.0 mm	6.0 mm	10.0 mm	9.0 mm
H2117Z3	M6 x 0.75	90°	18.0 mm	5.5 mm	3.7 mm	17.0 mm	6.0 mm	13.0 mm	9.0 mm

Common Parts
Parts with this designation are in wide distribution.

Alemite®
Alemite® is a registered trademark of Alemite, LLC, Johnson City, TN, USA.

Lincoln Industrial®
Lincoln Industrial® is a registered trademark of Lincoln Industrial (USA) Corp.

John Deere®
John Deere® is a registered trademark of Deere and Company, Moline, Illinois.

All manufacturer names and numbers are for cross reference identification purposes only. In no way are we implying that our parts were made by the manufacturers listed.
Prices, materials, dimensions, tolerances, designs and grades subject to change without notice. © G.L. Huyett 2019