SAFETY VENT


EXCEEDS 72 HR SALT SPRAY.

SAE J534

Safety vent fittings have a groove cut into the threads, which allows excess grease to escape to prevent overpressurization. Grease in the groove indicates maximum lubrication. While potentially messy, this is a cost-effective safety precaution.

H1930Z3


Straight Safety Vent
1/8"-27 PTF Spl. Extra Short
Long Shank



1930
5099
JD7805
AVAILABLE IN STAINLESS

H1925Z3


65° Angle Safety Vent
1/8"-27 PTF Spl. Short
Long Shank



1925-B


H1927Z3

Straight Safety Vent
1/4"-18 PTF SAE Short
Extra Long Shank




H1910

Straight Safety Vent
1/4"-28 SAE-LT
Standard Shank



H1909Z3

Straight Safety Vent
1/4"-28 SAE-LT
Standard Shank



1909
NO BALL CHECK

SPECIAL PARTS

DO YOU NEED A CUSTOM GREASE FITTING FOR YOUR OPERATION?

WE CAN MAKE IT, CALL OUR SALES TEAM TODAY!

Item #	Thread	Angle (E)	Overall Length (A)	Shank Length (B)	Min. Thread Length (C)	Overall Width (D)	Thread Diameter (F)	Swing Clearance (G)	Hex (H)
H1930Z3	1/8"-27	Straight	.73"	.28"	.22"	—	.39"	—	7/16"
H1925Z3	1/8"-27	65°	.86"	.30"	.22"	.72"	.39"	.50"	7/16"
H1927Z3	1/4"-18	Straight	.88"	.45"	.34"	—	.52"	—	9/16"
H1910	1/4"-28	Straight	.54"	.18"	.10"	—	.25"	—	5/16"
H1909Z3	1/4"-28	Straight	.54"	.21"	.10"	—	.25"	—	5/16"

Common Parts
Parts with this designation are in wide distribution.

Alemite®
Alemite® is a registered trademark of Alemite, LLC, Johnson City, TN, USA.

Lincoln Industrial®
Lincoln Industrial® is a registered trademark of Lincoln Industrial (USA) Corp.

John Deere®
John Deere® is a registered trademark of Deere and Company, Moline, Illinois.

All manufacturer names and numbers are for cross reference identification purposes only. In no way are we implying that our parts were made by the manufacturers listed.
Prices, materials, dimensions, tolerances, designs and grades subject to change without notice. © G.L. Huyett 2019

REVISED 03-19

TECHNICAL DRAWINGS ARE APPROXIMATE ACTUAL SIZE