TECHNICAL DRAWINGS ARE APPROXIMATE ACTUAL SIZE

BRITISH - 3/8"-19 BSPT

EXCEEDS 72 HR SALT SPRAY. 8,000 PSI MAX PRESSURE.

DIN 71412

The large threads on the 3/8"-19 BSPT fittings make them well suited for rugged applications like cold weather, heavy lubricants and environments which may damage smaller fittings. Please note, care should be used to not interchange 3/8"-19 BSPT and 3/8"-18 PTF fittings. These British tapered threads are covered by DIN 2999.

H2606

Straight
3/8"-19 BSPT
Standard Shank



H2607

45° Angle
3/8"-19 BSPT
Standard Shank



H2608

90° Angle
3/8"-19 BSPT
Standard Shank



ITEM #	THREAD	ANGLE (E)	OVERALL LENGTH (A)	SHANK LENGTH (B)	MIN. THREAD LENGTH (C)	OVERALL WIDTH (D)	THREAD DIAMETER (F)	SWING CLEARANCE (G)	HEX (H)
H2606	3/8"-19	STRAIGHT	.71"	.28"	.16"	□	.63"	□	17.0 MM
H2607	3/8"-19	45□	1.00"	.28"	.16"	.87"	.63"	.51"	17.0 MM
H2608	3/8"-19	90□	.79"	.28"	.16"	1.06"	.63"	.75"	17.0 MM

CONSIDER THIS...

CAUTION SHOULD BE USED WHEN MEASURING BRITISH THREADS, AS MANY COMMON BRITISH SIZES DIFFER FROM COMMON AMERICAN SIZES ONLY SLIGHTLY. MISMATCHED THREADS WILL PROVIDE AN INFERIOR ENGAGEMENT AND MAY RESULT IN FITTING FAILURE.

Common Parts
Parts with this designation are in wide distribution.
Alemite®
Alemite® is a registered trademark of Alemite, LLC, Johnson City, TN, USA.
Lincoln Industrial®
Lincoln Industrial® is a registered trademark of Lincoln Industrial (USA) Corp.
John Deere®
John Deere® is a registered trademark of Deere and Company, Moline, Illinois.

All manufacturer names and numbers are for cross reference identification purposes only. In no way are we implying that our parts were made by the manufacturers listed.
Prices, materials, dimensions, tolerances, designs and grades subject to change without notice. © G.L. Huyett 2011