FLUSH TYPE

EXCEEDS 72 HR SALT SPRAY.
8,000 PSI MAX PRESSURE.

DIN 3405

Flush type fittings are ideal for applications where protruding greasing nipples may be impractical. Metric flush type fittings are available in both parallel and taper thread. Our angled flush type fittings possess tapered threads.

TECHNICAL DRAWINGS ARE APPROXIMATE ACTUAL SIZE

H2406
Straight Flush Type
M6 x 1.0 Parallel Thread
Standard Shank



AVAILABLE IN STAINLESS

H2407
45° Angle Flush Type
M6 x 1.0 Taper Thread
Standard Shank



H2408
90° Angle Flush Type
M6 x 1.0 Taper Thread
Standard Shank



H2403
Straight Flush Type
M8 x 1.0 Parallel Thread
Standard Shank



AVAILABLE IN STAINLESS

H2412
Straight Flush Type
M8 x 1.25 Parallel Thread
Standard Shank



H2409
Straight Flush Type
M10 x 1.0 Parallel Thread
Standard Shank



AVAILABLE IN STAINLESS

H2421
Straight Flush Type
M10 x 1.5 Parallel Thread
Standard Shank



H2424
Straight Flush Type
M12 x 1.5 Parallel Thread
Standard Shank



ITEM #	THREAD	THREAD TYPE	ANGLE	OVERALL LENGTH (A)	SHANK LENGTH (B)	MIN. THREAD LENGTH (C)	THREAD DIAMETER (F)	HEX (H)
H2406	M6 X 1.0	PARALLEL	STRAIGHT	8.5 MM	5.5 MM	3.7 MM	6.0 MM	7.0 MM
H2407	M6 X 1.0	TAPER	45°	18.0 MM	5.5 MM	3.7 MM	6.0 MM	9.0 MM SQ.
H2408	M6 X 1.0	TAPER	90°	18.0 MM	5.5 MM	3.7 MM	6.0 MM	9.0 MM SQ.
H2403	M8 X 1.0	PARALLEL	STRAIGHT	9.5 MM	6.5 MM	3.7 MM	7.9 MM	9.0 MM
H2404	M8 X 1.0	TAPER	45°	16.0 MM	5.5 MM	3.7 MM	8.0 MM	9.0 MM SQ.
H2405	M8 X 1.0	TAPER	90°	18.0 MM	5.5 MM	3.7 MM	8.0 MM	9.0 MM SQ.
H2412	M8 X 1.25	PARALLEL	STRAIGHT	9.5 MM	6.5 MM	3.7 MM	7.9 MM	9.0 MM
H2409	M10 X 1.0	PARALLEL	STRAIGHT	9.5 MM	6.5 MM	3.7 MM	9.8 MM	11.0 MM
H2410	M10 X 1.0	TAPER	45°	16.5 MM	5.5 MM	3.7 MM	10.0 MM	11.0 MM SQ.
H2411	M10 X 1.0	TAPER	90°	18.0 MM	5.5 MM	3.7 MM	10.0MM	11.0 MM SQ.
H2421	M10 X 1.5	PARALLEL	STRAIGHT	9.5 MM	6.5 MM	3.7 MM	9.8MM	11.0 MM
H2424	M12 X 1.5	PARALLEL	STRAIGHT	14.0 MM	9.5 MM	4.2 MM	11.8 MM	14.0 MM

Common Parts
Parts with this designation are in wide distribution.

Alemite®
Alemite® is a registered trademark of Alemite, LLC, Johnson City, TN, USA.

Lincoln Industrial®
Lincoln Industrial® is a registered trademark of Lincoln Industrial (USA) Corp.

John Deere®
John Deere® is a registered trademark of Deere and Company, Moline, Illinois.

All manufacturer names and numbers are for cross reference identification purposes only. In no way are we implying that our parts were made by the manufacturers listed.
Prices, materials, dimensions, tolerances, designs and grades subject to change without notice. © G.L. Huyett 2011

ITEMS ARE NOT PICTURED.

REVISED 06-11