EURO DIN™
785.392.3017 FAX 785.392.2845
BOX 232 • MINNEAPOLIS, KS • 67467
www.huyett.com
G.L.HUYETT

BUTTON HEAD

EXCEEDS 72 HR SALT SPRAY. 8,000 PSI MAX PRESSURE.

DIN 3404

Button head fittings are designed with a large flat head which makes them suitable for rugged environments or applications where horizontal access to the greasing point is required. Parallel threads ensure fittings seat flush against the shoulder. G.L. Huyett's standard button head couplers, page 120, are specially engineered to accommodate both metric and imperial button head fittings.

TECHNICAL DRAWINGS ARE APPROXIMATE ACTUAL SIZE

H2303
Button Head - Standard
M8 x 1.0 Parallel Thread
Ball Check



AVAILABLE IN STAINLESS

H2304
Button Head - Standard
M8 x 1.25 Parallel Thread
Ball Check



AVAILABLE IN STAINLESS

H2309
Button Head - Standard
M10 x 1.0 Parallel Thread
Ball Check



AVAILABLE IN STAINLESS

H2315
Button Head - Standard
M12 x 1.5 Parallel Thread
Ball Check



AVAILABLE IN STAINLESS

H2316
Button Head - Standard
M12 x 1.75 Parallel Thread
Ball Check



AVAILABLE IN STAINLESS

H2319
Button Head - Standard
M14 x 1.5 Parallel Thread
Ball Check



H2323
Button Head - Standard
M16 x 1.5 Parallel Thread
Ball Check



H2326
Button Head - Heavy Duty
M16 x 1.5 Parallel Thread
Ball Check



HEAVY DUTY BUTTON HEAD

ITEM #	THREAD	OVERALL LENGTH (A)	SHANK LENGTH (B)	MIN. THREAD LENGTH (C)	THREAD DIAMETER (F)	HEX (H)	VALVE SYSTEM
H2306	M6 X 1.0	17.0 MM	6.0 MM	3.1 MM	6.0 MM	17.0 MM	BALL CHECK
H2303	M8 X 1.0	17.0 MM	6.0 MM	3.1 MM	7.9 MM	17.0 MM	BALL CHECK
H2304	M8 X 1.25	17.0 MM	6.0 MM	3.1 MM	7.9 MM	17.0 MM	BALL CHECK
H2309	M10 X 1.0	17.0 MM	6.0 MM	3.1 MM	9.8 MM	17.0 MM	BALL CHECK
H2311	M10 X 1.5	17.0 MM	6.0 MM	3.1 MM	9.8 MM	17.0 MM	BALL CHECK
H2315	M12 X 1.5	17.0 MM	6.0 MM	3.1 MM	11.8 MM	17.0 MM	BALL CHECK
H2316	M12 X 1.75	17.0 MM	6.0 MM	3.1 MM	11.2 MM	17.0 MM	BALL CHECK
H2319	M14 X 1.5	17.0 MM	6.0 MM	3.1 MM	13.1 MM	17.0 MM	BALL CHECK
H2323	M16 X 1.5	18.0 MM	7.0 MM	4.0 MM	15.6 MM	17.0 MM	BALL CHECK
H2326	M16 X 1.5	21.0 MM	7.0 MM	4.0 MM	15.6 MM	22.0 MM	BALL CHECK

Common Parts
Parts with this designation are in wide distribution.

Alemite®
Alemite® is a registered trademark of Alemite, LLC, Johnson City, TN, USA.

Lincoln Industrial®
Lincoln Industrial® is a registered trademark of Lincoln Industrial (USA) Corp.

John Deere®
John Deere® is a registered trademark of Deere and Company, Moline, Illinois.

All manufacturer names and numbers are for cross reference identification purposes only. In no way are we implying that our parts were made by the manufacturers listed.
Prices, materials, dimensions, tolerances, designs and grades subject to change without notice. © G.L. Huyett 2011

ITEMS ARE NOT PICTURED.

REVISED 06-11