
M12

EXCEEDS 72 HR SALT SPRAY.
8,000 PSI MAX PRESSURE.


DIN 71412

12.0 mm threads are commonly used in heavy-duty applications and on large bearings. The larger size makes them well suited for cold weather applications and for use with heavy lubricants. Coarse threads are recommended for soft materials such as aluminum.


H2142
Straight
M12 x 1.0 Taper Thread
Standard Shank




H2143
45° Angle
M12 x 1.0 Taper Thread
Standard Shank




H2144
90° Angle
M12 x 1.0 Taper Thread
Standard Shank



H2145
Straight
M12 x 1.25 Taper Thread
Standard Shank




H2124
Straight
M12 x 1.5 Taper Thread
Standard Shank



AVAILABLE IN STAINLESS

H2125
45° Angle
M12 x 1.5 Taper Thread
Standard Shank



ITEM #	THREAD	ANGLE (E)	OVERALL LENGTH (A)	SHANK LENGTH (B)	MIN. THREAD LENGTH (C)	OVERALL WIDTH (D)	THREAD DIAMETER (F)	SWING CLEARANCE (G)	HEX (H)
H2142	M12 X 1.0	STRAIGHT	17.5 MM	6.5 MM	3.1 MM	□	12.0 MM	□	14.0 MM
H2143	M12 X 1.0	45□	22.5 MM	6.5 MM	3.1 MM	19.0 MM	12.0 MM	12.0 MM	14.0 MM
H2144	M12 X 1.0	90□	22.0 MM	6.5 MM	3.1 MM	23.0 MM	12.0 MM	16.0 MM	14.0 MM
H2145	M12 X 1.25	STRAIGHT	17.5 MM	6.5 MM	3.1 MM	□	12.0 MM	□	14.0 MM
H2124	M12 X 1.5	STRAIGHT	17.5 MM	6.5 MM	3.1 MM	□	12.0 MM	□	14.0 MM
H2125	M12 X 1.5	45□	22.5 MM	6.5 MM	3.1 MM	19.0 MM	12.0 MM	12.0 MM	14.0 MM

TECHNICAL DRAWINGS ARE APPROXIMATE ACTUAL SIZE

Common Parts
Parts with this designation are in wide distribution.

Alemite®
Alemite® is a registered trademark of Alemite, LLC, Johnson City, TN, USA.

Lincoln Industrial®
Lincoln Industrial® is a registered trademark of Lincoln Industrial (USA) Corp.

John Deere®
John Deere® is a registered trademark of Deere and Company, Moline, Illinois.

All manufacturer names and numbers are for cross reference identification purposes only. In no way are we implying that our parts were made by the manufacturers listed.
Prices, materials, dimensions, tolerances, designs and grades subject to change without notice. © G.L. Huyett 2011

REVISED 06-11