



METRIC LOCKNUT

MANUFACTURER CROSS-REFERENCE

INDEX PAGE 236.

Whittet-Higgins KM

KM	BORE	LOCKNUT DIMENSIONS					WEIGHT	MATERIAL	
	Bearing Bore Nominal (N)	Pitch Length	Major Diameter	Outside Diameter Max. (OD)	Thickness (T)	Nut Face Diameter Max. (Dc)	Kg per 100 Pieces	Low Carbon	Mating Lockwasher
KM-00	10	.75	10	18	4	13.5	0.5682		MB-00
-01	12	1.00	12	22	4	17.0	0.8523		-01
-02	15		15	25	5	21.0	1.1364		-02
-03	17		17	28	5	24.0	1.4205		-03
-04	20		20	32	6	26.0	1.9886		-04
-045	22		22	34	6	28.0	2.2727		-045
-05	25	1.50	25	38	7	32.0	3.1250		-05
-055	28		28	42	7	36.0	3.6932		-055
-06	30		30	45	7	38.0	4.5455		-06
-065	32		32	48	8	40.0	5.6818		-065
-07	35		35	52	8	44.0	6.5341		-07
-08	40		40	58	9	50.0	9.0909		-08
-09	45		45	65	10	56.0	12.2159		-09
-10	50		50	70	11	61.0	14.7727		-10
-11	55	2.00	55	75	11	67.0	16.4773		-11
-12	60		60	80	11	73.0	17.8977		-12
-13	65		65	85	12	79.0	21.0227		-13
-14	70		70	92	12	85.0	25.0000		-14
-15	75		75	98	13	90.0	15.3409		-15
-16	80		80	105	15	95.0	19.8864		-16
-17	85		85	110	16	102.0	46.0227		-17
-18	90		90	120	16	108.0	56.8182		-18
-19	95		95	125	17	113.0	64.7727		-19
-20	100		100	130	18	120.0	72.7273		-20
-21	105		105	140	18	126.0	87.5000		-21
-22	110		110	145	19	133.0	97.7273		-22
-23	115		115	150	19	137.0	90.9091		-23
-24	120		120	155	20	138.0	107.9545		-24
-25	125		125	160	21	148.0	119.0000		-25
-26	130		130	165	21	149.0	125.0000		-26
-27	135		135	175	22	160.0	155.0000		-27
-28	140		140	180	22	160.0	159.0909		-28
-29	145		145	190	24	171.0	200.0000		-29
-30	150		150	195	24	171.0	207.3864		-30
-31	155	3.00	155	200	25	182.0	221.0000		-31
-32	160		160	210	25	182.0	255.6818		-32
-33	165		165	210	26	193.0	284.0909		-33
-34	170		170	220	26	193.0	280.0000		-34
-36	180		180	230	27	203.0	305.1136		-36
KM-40	200		200	250	29	226.0	373.2955		MB-40

MATING LOCKWASHER DESCRIPTIONS ON PAGE 221.

KM

AXIAL ASSEMBLY

DESCRIPTION

These metric locknuts fall under ISO-2982. Fully interchangeable with most standard metric locknuts.

HOW TO IDENTIFY


1. Verify the bearing bore nominal (N).
2. Determine the major diameter (Dm), outside diameter (OD), and thickness (T) of the part.
3. Find the part in the chart above.

GENERAL USE



UNCOMMON

REQUIRES A KEYWAY.



LET OUR SHOP CUT IT FOR YOU!

SEE PAGE 218.

MOST SIZES AVAILABLE IMMEDIATELY • $2 LINE REQUESTED • CALL PLANT FOR QUANTITY DISCOUNTS

All manufacturer names and numbers are for identification purposes only. In no way are we implying that our parts were made by the manufacturers listed above.
Prices, materials, tolerances, and grades subject to change without notice.
© G.L. Huyett 2004