TECHNICAL DRAWINGS ARE APPROXIMATE ACTUAL SIZE

1/8"-27 PTF SAE J534 BRASS

Brass has excellent corrosion resistance compared to stainless steel, but it is less resistant to wear.

H1610B

Straight - Brass
1/8"-27 PTF Spl. Extra Short
Standard Shank



AVAILABLE IN STAINLESS



ITEM #	THREAD	ANGLE (E)	OVERALL LENGTH (A)	SHANK LENGTH (B)	MIN. THREAD LENGTH (C)	OVERALL WIDTH (D)	THREAD DIAMETER (F)	SWING CLEARANCE (G)	HEX (H)
H1610B	1/8"-27	STRAIGHT	.66"	.28"	.18"		.39"		7/16"

PARALLEL THREADS SAE J534 BRASS

The corrosion resistance of brass fittings makes them ideal for use on water pumps and fire trucks. Their attractive color also makes them suited as decorative features for antique equipment or custom vehicles.

H1711B

Straight - Brass
5/16"-24 UNF
Short Shank



AVAILABLE IN STAINLESS

H1710B

Straight - Brass
3/8"-24 UNF
Standard Shank



AVAILABLE IN STAINLESS

ITEM #	THREAD	ANGLE (E)	OVERALL LENGTH (A)	SHANK LENGTH (B)	MIN. THREAD LENGTH (C)	OVERALL WIDTH (D)	THREAD DIAMETER (F)	SWING CLEARANCE (G)	HEX (H)
H1711B	5/16"-24	STRAIGHT	.66"	.20"	.12"		.31"		3/8"
H1710B	3/8"-24	STRAIGHT	.64"	.24"	.14"		.37"		7/16"

Common Parts — Parts with this designation are in wide distribution.

Alemite® — Alemite® is a registered trademark of Alemite, LLC, Johnson City, TN, USA.

Lincoln Industrial® — Lincoln Industrial® is a registered trademark of Lincoln Industrial (USA) Corp.

John Deere® — John Deere® is a registered trademark of Deere and Company, Moline, Illinois.

All manufacturer names and numbers are for cross reference identification purposes only. In no way are we implying that our parts were made by the manufacturers listed.
Prices, materials, dimensions, tolerances, designs and grades subject to change without notice. © G.L. Huyett 2011