

PRODUCT INFORMATION PACKET

marathon[®]
Motors

Model No: 048A11O1875
Catalog No: X039
3/4,1140,OPEN,48Y,1/60/460
Direct Drive



Regal and Marathon are trademarks of Regal Beloit Corporation or one of its affiliated companies.
©2018 Regal Beloit Corporation, All Rights Reserved. MC017097E

REGAL





Nameplate Specifications

Output HP	0.75 Hp	Output KW	0.56 kW
Frequency	60 Hz	Voltage	460 V
Current	2.1 A	Speed	1075 rpm
Service Factor	1	Phase	1
Efficiency	64 %	Duty	CONTINUOUS
Insulation Class	B	Design Code	NO DESIGN CODE
KVA Code	B	Frame	48Z
Enclosure	OPAO	Overload Protector	AUT LCK RTR ONLY
Ambient Temperature	40 °C	Drive End Bearing Size	6203
Opp Drive End Bearing Size	6203	UL	Recognized
CSA	Y	CE	N
IP Code	10		

Technical Specifications

Electrical Type	PSC 2 SPEED	Starting Method	ACROSS THE LINE
Poles	6	Rotation	SELECTIVE CCW
Mounting	ROUND-EXTENDED STUDS	Motor Orientation	HORIZONTAL
Drive End Bearing	BALL	Opp Drive End Bearing	BALL
Frame Material	ROLLED STEEL	Shaft Type	SGL SPL EXT
Overall Length	12.44 in	Frame Length	5 in
Shaft Diameter	0.5 in	Shaft Extension	6.06 in
Assembly/Box Mounting	F1 ONLY		
Outline Drawing	A-SS400491-500	Connection Diagram	9580309

TERM. END




LEAD DESCRIPTION:

1 BLACK, 1 RED & 1 WHITE LEAD WITH .50 BARE WIRE STRIP 27.00" LONG.

2 BROWN CAPACITOR LEADS WITH .50" BARE WIRE STRIP 27.00" LONG BROWN WITH WHITE MARK IS COMMON TO WHITE LEAD.

REVERSING LEADS ARE MOLDED INTO MATING PULL APART PLUGS 1 PURPLE, AND 1 YELLOW PER PLUG 5.00" LONG.

GREEN GROUND LEAD WITH TERM. FOR #10 SCREW 12.00" LONG.



DASH	FRAME	C	A
400	48Y	11.44	4.50
425	48Y	11.69	4.75
450	48Y	11.94	5.00
475	48Y	12.19	5.25
500	48Y	12.44	5.50

NO.	REVISION	BY & DATE	CHK	ANG	TOLERANCES UNLESS SPECIFIED
5	UPDATED DRAWING	RJW 04-13-2007		DEC.	INCHES
4	REDRAWN IN AUTOCAD	TAT 08-03-2004	ML	.X	±.1
3	REVISED NAME PLATE LOCATION CN 29400-13	CAV 01-18-2000		.XX	±.03
2	BLACK, RED, & WHITE WAS 30" MU26803	CAV 09-10-1999		.XXX	±.005
1	NEW DRAWING MU26799	TRB 09-03-1999		.XXXX	±.0005
					±.7'30"

	DRAWN TRB 09-01-1999	
	CHK ML 09-02-1999	
	APPD RJS 09-03-1999	
	SCALE 3=8	
	REF	
MAT'L.		FMF
FINISH		PREV

THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT

RFP

DIST WP

CAD FILE ss400491



SIZE

A

DRAWING NO. PAGE OF REV.

SS400491

5



				✓ MAX. SURFACE ROUGHNESS UNLESS NOTED OTHERWISE	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOL. ON XX±.02 XXX±.005 XXXX±.0005 ANGLES± 7°30"			
				MATL SPEC		DRAWN BY	TRB	09-01-1999
				FINISH		CHKD BY	ML	09-02-1999
					WAUSAU, WISCONSIN 54401	APPD BY	RJS	09-03-1999
REV	DATE	CHANGE	NAME	PART NAME CONNECTION DIAGRAM INSERT				DRWG NO A- 9580309
		SHOP BOOK	PURCHASED	DISTRIBUTION - WA - LB - WP - LM		CADD FILE NO.		9580309

ERROR: syntaxerror
OFFENDING COMMAND: --nostringval--

STACK:

225 /agrave
224 /germandbls
223 /Thorn
222 /Yacute
221 /Udieresis
220 /Ucircumflex
219 /Uacute
218 /Ugrave
217 /Oslash
216 /multiply
215 /Odieresis
214 /Otilde
213 /Ocircumflex
212 /Oacute
211 /Ograve
210 /Ntilde
209 /Eth
208 /Idieresis
207 /Icircumflex
206 /Iacute
205 /Igrave
204 /Edieresis
203 /Ecircumflex
202 /Eacute
201 /Egrave
200 /Ccedilla
199 /AE
198 /Aring
197 /Adieresis
196 /Atilde
195 /Acircumflex
194 /Aacute
193 /Agrave
192 /questiondown

CERTIFICATION DATA SHEET

Model#: 48A1101875 A **WINDING#:** PE4861810 NONE 4
CONN. DIAGRAM: 9580309 **ASSEMBLY:** F1 ONLY
OUTLINE: A-SS400491-500

TYPICAL MOTOR PERFORMANCE DATA

HP	KW	SYNC. RPM	F.L. RPM	FRAME	ENCLOSURE	KVA CODE	DESIGN
3/4	.56	1200	1075	48Z	OPAO	B	NO DESIGN CODE

PH	Hz	VOLTS	FL AMPS	START TYPE	DUTY	INSL	S.F	AMB°C	ELEVATION
1	60	460	2.1	ACROSS THE LINE	CONTINUOUS	B3	1.0	40	3300

FULL LOAD EFF: 64	3/4 LOAD EFF: -	1/2 LOAD EFF: -	GTD. EFF	ELEC. TYPE	NO LOAD AMPS
FULL LOAD PF: 90	3/4 LOAD PF: -	1/2 LOAD PF: -	0	PSC 2 SPEED	.5

F.L. TORQUE	LOCKED ROTOR AMPS	L.R. TORQUE	B.D. TORQUE	F.L. RISE°C
- LB-FT	3.7	14.4 LB-FT 0	58 LB-FT 0	0

SOUND PRESSURE @ 3 FT.	SOUND POWER	ROTOR WK^2	MAX. WK^2	SAFE STALL TIME	STARTS /HOUR	APPROX. MOTOR WGT
- dBA	- dBA	0 LB-FT^2	- LB-FT^2	- SEC.	-	0 LBS.

*** SUPPLEMENTAL INFORMATION ***

DE BRACKET TYPE	ODE BRACKET TYPE	MOUNT TYPE	ORIENTATION	SEVERE DUTY	HAZARDOUS LOCATION	DRIP COVER	SCREENS	PAINT
STANDARD	STANDARD	ROUND-EXTENDED STUDS	HORIZONTAL	FALSE	NONE	FALSE	NONE	GRAY (POWDER)

BEARINGS		GREASE	SHAFT TYPE	SPECIAL DE	SPECIAL ODE	SHAFT MATERIAL	FRAME MATERIAL
DE	OPE						
BALL	BALL						
6203	6203	BEACON 325	SGL SPL EXT	0.500 x 6.00 WITH 5.50 DBL FULL FLATS	NONE	1144 STRESSPROOF (C-223)	ROLLED STEEL

THERMO-PROTECTORS				THERMISTORS	CONTROL	SPACE /n HEATERS
THERMOSTATS	PROTECTORS	WDG RTDs	BRG RTDs			
NONE	AUT LCK RTR ONLY	NONE	NONE	NONE	FALSE	NONE VOLTS

If Inverter equals NONE, contact factory for further information

*
N
O
T
E
*

INVERTER TORQUE: NONE
INV. HP SPEED RANGE: NONE
ENCODER: NONE
NONE NONE
NONE NONE PPR
BRAKE: NONE NONE
NONE P/N NONE
NONE NONE
NONE FT-LB NONE V NONE Hz

DATE: 06/27/2017 04:37:54 AM
 FORM 3531 REV.3 02/07/99
 ** Subject to change without notice.

