## PRODUCT INFORMATION PACKET



Model No: 048A11O1109 Catalog No: X222 1/3,1075,OPAO,48Y,1/60/230 Other Purpose



Regal and Marathon are trademarks of Regal Beloit Corporation or one of its affiliated companies.

©2018 Regal Beloit Corporation, All Rights Reserved. MC017097E





## **Nameplate Specifications**

Output HP	0.33 Hp	Output KW	0.25 kW
Frequency	60 Hz	Voltage	230 V
Current	2.6 A	Speed	1075 rpm
Service Factor	1	Phase	1
Efficiency	66 %	Duty	CONTINUOUS
Insulation Class	В	Design Code	NO DESIGN CODE
KVA Code	С	Frame	48Y
Enclosure	OPAO	Overload Protector	AUT LCK RTR ONLY
Ambient Temperature	40 °C	Drive End Bearing Size	6203
Opp Drive End Bearing Size	6203	UL	Recognized
CSA	Υ	CE	N
IP Code	10		

## **Technical Specifications**

Electrical Type	PSC 2 SPEED	Starting Method	ACROSS THE LINE
Poles	6	Rotation	SELECTIVE CCW
Mounting	THREE LUG MOUNT	Motor Orientation	HORIZONTAL
Drive End Bearing	BALL	Opp Drive End Bearing	BALL
Frame Material	ROLLED STEEL	Shaft Type	SGL SPL EXT
Overall Length	8.25 in	Frame Length	4.25 in
Shaft Diameter	0.5 in	Shaft Extension	3.06 in
Assembly/Box Mounting	F1 ONLY		
Outline Drawing	A-SS403712-425	Connection Diagram	6906489

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created: 04/05/2018



