



THREADED ACCESSORIES

Fig. 20 & 21 CONTINUOUS THREADED ROD

Fig. 20* PLAIN

Fig. 21 ELECTRO-GALVANIZED



*Available in stainless steel. To order, specify 304 or 316 and add suffix SS to figure number.
Price on request.

FUNCTION: Useful in applications where stud lengths cannot be predetermined.

MATERIAL: Low carbon steel

ORDERING: Specify rod size, length and figure number.

Rod Size	Packaging Feet Per Bundle						Max. Rec. Load				Wt. Per Foot	
							650°F (343°C)		750°F (399°C)			
	6ft.	(1.83)	10ft.	(3.05)	12ft.	(3.66)	lbs.	kN	lbs.	kN	lbs.	kg
1/4 -20	300	(91.44)	500	(152.4)	600	(182.88)	240	(1.07)	188	(0.84)	.12	(.05)
3/8 -16	150	(45.72)	250	(76.2)	240	(73.15)	730	(3.25)	572	(2.54)	.29	(.13)
1/2 -13	72	(21.95)	120	(36.58)	144	(43.90)	1350	(6.01)	1057	(4.70)	.54	(.25)
5/8 -11	48	(14.63)	80	(24.38)	96	(29.26)	2160	(9.61)	1692	(7.52)	.83	(.38)
3/4 -10	30	(9.14)	50	(15.24)	60	(18.29)	3230	(14.37)	2530	(11.25)	1.25	(.57)
7/8 -9	24	(7.32)	40	(12.19)	48	(14.63)	4480	(19.93)	3508	(15.61)	1.65	(.75)
1-8	12	(3.66)	20	(6.10)	24	(7.32)	5900	(26.24)	4620	(20.55)	2.25	(1.02)

Unless otherwise specified, all dimensions on drawings and in charts are in inches and dimensions shown in parentheses are in millimeters.