CADDY PYRAMID ST Fixed Strut Support – PSF16D












- Provides superior support for pipe, conduit, duct, cable tray and equipment
- Foam bottom offers low abrasion interface for better roof membrane protection
- Compatible with roof surfaces including single ply, bituminous, metal and spray foam
- Provides superior load distribution, even with varying rooftop surfaces
- Ready to use out of the box, saving installation time and labor
- Multiple sizes and load ratings offer the ability to tailor the solution to the application
- Easy to transport to the roof
- Hot-dip galvanized and UV stabilized for long lasting performance
- Supports green building requirements; thermoplastic bases are made from recycled material and can contribute to earning LEED credits





D. W. J.	DCF4/D
Part Number	PSF16D
Material	Polyethylene Polypropylene Steel
Finish	Hot-Dip Galvanized
Temperature	-50 to 150 °F
Static Load Safety Factor	3:1
Length 1 (L1)	16"
Length 2 (L2)	19"
Height (H)	6.4"
Width (W)	8"
Surface Area	142 in²
Unit Weight	5 lb
Static Load (F)	1,500 lb
Standard Packaging Quantity	5 pc
UPC	78285684306
EAN-13	8711893139679

Static load at 73.1 kPa (10.6 psi) roof loading. Contact project or roofing engineer for maximum allowable load on individual project roof system.





