




Metal Pressure Clip

PKM - Series



Max Spacing 5 ft [1.5m]



Part Number	Article Number	Capacity**	Hole Size in [mm]	Installed
PKM16H3	182046	Max 16 cables	.187 [4.75]	Gas or Powder Actuated Tools
PKM10H3	182044	Max 10 cables		
PKM16H6	182047	Max 16 cables	.280 [7.11]	1/4" or M6 stud, self tapping screw, or drive pin
PKM10H6	182045	Max 10 cables		
Fire-Rated Assemblies - Use PKMINSERT [182051]*				
PKM16H6IN	182049	See abP Certificate*	.280 [7.11]	See abP Certificate*
PKM10H6IN	182048			
PKMINSERT	182051			

* abP certificate is available on product webpage at www.nVent.com or your nVent customer service representative for fire rated applications

** Fill rate based on 3x1.5x10 mm cable

*** For 13mm diameter cables, place large 6mm washer between fastener and structure and reduce fill rate by 2 cables per side

WARNING:

1. nVent products shall be installed and used only as indicated in nVent product instruction sheets and training materials. Instruction sheets are available at www.nVent.com and from your nVent customer service representative.
2. nVent products must never be used for a purpose other than the purpose for which they were designed or in a manner that exceeds specified load ratings.
3. All instructions must be completely followed to ensure proper and safe installation and performance.
4. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and/or death, and void your warranty.
5. Products that are manufactured using spring steel components shall be used only in a non-corrosive indoor environment.
6. All pipe supports, hangers, intermediate components and structural attachments must ONLY be used as described herein and are NEVER to be used for any other purpose.

NOTE: All load ratings are for static conditions and do not account for dynamic loading such as wind, water or seismic loads, unless otherwise noted.

The customer is responsible for:

- a. Conformance to all governing codes.
- b. The integrity of structures to which the products are attached, including their capability of safely accepting the loads imposed, as evaluated by a qualified engineer.
- c. Using appropriate industry standard hardware as noted above.

SAFETY INSTRUCTIONS:

All governing codes and regulations and those required by the job site must be observed. Always use appropriate safety equipment such as eye protection, hard hat, and gloves as appropriate to the application.

nVent, CADDY, ERICO CADWELD, ERICO CRITEC, ERICO, ERIFLEX, and LENTON are owned by nVent or its global affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.