


# Hammer-On Flange Clip, Bottom Mount with Stud – M1318S



- Can be used to support boxes, fixtures or other applications from beam flanges
- Captive threaded stud minimizes the need for additional hardware
- Assorted attachment points provided to reduce inventory
- Requires only a hammer to install



|                             |                    |
|-----------------------------|--------------------|
| Part Number                 | M1318S             |
| Material                    | Spring Steel       |
| Finish                      | nVent CADDY Armour |
| Flange Thickness (FT)       | 13/16" – 1 1/8"    |
| Rod Size (RS)               | 1/4"               |
| Screw Diameter (Sc)         | 1/4"               |
| Screw Length (L)            | 3/8"               |
| Static Load 1 (F1)          | 100 lb             |
| Static Load 2 (F2)          | 75 lb              |
| Static Load 3 (F3)          | 25 lb              |
| Certifications              | cULus              |
| Standard Packaging Quantity | 50 pc              |
| UPC                         | 78285695358        |

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.erico.com](http://www.erico.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

