


634 Pipe Saddle for 3" Insulation – 6342400PL



- Designed for high temperature service or where heat losses are to be kept at a minimum and to protect insulation against damage at the point of support
- Conforms with Federal Specification WW-H-171 (Type 40A or 40B), Manufacturers Standardization Society ANSI®/MSS-SP-58 (Type 39)



| | |
|-----------------------------|-------------|
| Part Number | 6342400PL |
| Material | Steel |
| Finish | Plain |
| Pipe Size | 24" |
| Length (L) | 12" |
| Insulation Thickness | 3" |
| Standard Packaging Quantity | 50 pc |
| UPC | 78285637144 |

| Part Number | Pipe Size | Cover Thickness | Size of Pipe Roll for Model # | | | Center Line of Pipe to Outside of Saddle | Center Line of Pipe to Center Line of Roll for Model # | | | Static Load |
|-------------|-----------|-----------------|-------------------------------|-----|-----------|--|--|-----------|----------|-------------|
| | | | 605, 615 | 610 | 617, 619 | | 605, 615 | 610 | 617, 619 | |
| 6340200PL | 2" | 3 1/8" | 8" | 8" | 4" - 6" | 4 11/16" | 5 1/2" | 5 1/2" | 5 1/2" | 1,800 lb |
| 6340250PL | 2 1/2" | 3 3/8" | 8" | 10" | 4" - 6" | 4 15/16" | 5 11/16" | 5 13/16" | 5 9/16" | 1,800 lb |
| 6340300PL | 3" | 3 1/16" | 8" | 10" | 8" - 10" | 5" | 5 15/16" | 5 15/16" | 6" | 1,800 lb |
| 6340350PL | 3 1/2" | 3 5/16" | 10" | 10" | 8" - 10" | 5 1/2" | 6 7/16" | 6 7/16" | 6 1/2" | 1,800 lb |
| 6340500PL | 4" | 3 1/16" | 10" | 10" | 8" - 10" | 5 9/16" | 6 1/2" | 6 1/2" | 7 1/2" | 1,800 lb |
| | 5" | 3 1/16" | 10" | 12" | 8" - 10" | 6 1/8" | 7 1/16" | 7 3/16" | 7 3/16" | 1,800 lb |
| 6340800PL | 6" | 3" | 12" | 12" | 8" - 10" | 6 9/16" | 7 5/8" | 7 5/8" | 7 5/8" | 1,800 lb |
| | 8" | 3 1/8" | 14" | 16" | 12" - 14" | 7 5/8" | 8 15/16" | 8 15/16" | 8 11/16" | 1,800 lb |
| 6341000PL | 10" | 3 1/16" | 16" | 18" | 16" - 20" | 8 7/8" | 10 5/16" | 10 7/8" | 10 3/16" | 1,800 lb |
| 6341200PL | 12" | 3 1/16" | 18" | 20" | 16" - 20" | 9 11/16" | 9 11/16" | 11 3/16" | 11 1/16" | 5,000 lb |
| 6341400PL | 14" | 3" | 18" | 20" | 16" - 20" | 10 1/4" | 10 1/4" | 11 11/16" | 11 1/8" | 5,000 lb |
| 6341600PL | 16" | 3" | 24" | - | 22" - 24" | 11 3/16" | 13" | - | 12 9/16" | 7,200 lb |



| Part Number | Pipe Size | Cover Thickness | Size of Pipe Roll for Model # | | | Center Line of Pipe to Outside of Saddle | Center Line of Pipe to Center Line of Roll for Model # | | | Static Load |
|-------------|-----------|-----------------|-------------------------------|-----|-----------|--|--|-----|-----------|-------------|
| | | | 605, 615 | 610 | 617, 619 | | 605, 615 | 610 | 617, 619 | |
| 6341800PL | 18" | 3" | 24" | - | 22" - 24" | 12 5/16" | 14 1/4" | - | 13 11/16" | 7,200 lb |
| 6342000PL | 20" | 3" | 24" | - | 22" - 24" | 13 1/2" | 15 7/16" | - | 14 15/16" | 7,200 lb |
| 6342400PL | 24" | 3" | 30" | - | 26" - 30" | 15 3/8" | 18 3/16" | - | 17 1/8" | 7,200 lb |

Maximum recommended loads are applicable only when the saddle is used on a flat bearing surface and tack welded to the pipe. When a saddle is used with a pipe roll, the maximum load given for the pipe roll applies to the saddle.

Install in accordance with applicable code.

ANSI is a registered trademark of American National Standards Institute.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair. All rights reserved.

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.

