


nVent CADDY Rod Lock Spring Steel Rod Hanger with Offset Bracket – 4QT10



- Suspends threaded rod from vertical structures such as laminated wood or concrete beams, joists, ceilings and walls
- Easy "push-to-install" design allows installers to simply push the threaded rod through the mounting hole, instantly holding it in position
- Prefabricated assemblies easily lift and lock into place, helping to save time and money
- Works with slightly damaged threads and minor burrs on threaded rod ends
- Design includes a release mechanism that works with pliers



Part Number	4QT10
Material	Spring Steel Steel
Finish	nVent CADDY Armour Electrogalvanized
Rod Size (RS)	1/4"
Hole Size (HS)	0.28"
A	0.84"
Static Load (F)	75 lb
Certifications	cULus
Standard Packaging Quantity	100 pc
UPC	78480535059

Loads indicated are for nVent CADDY Fasteners only.
Method of attachment to structure must be evaluated separately.

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2021 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

