
## nVent CADDY Cat CM Double U-Hook, Wall Mount – UTS200CATCM



- Provides high volume capacity with easy side-load cable installation
- Cantilever mounting allows U-Hooks to be mounted to walls and columns
- Provides optimal support for high-performance data cable, up to and including Cat 5e, Cat 6, Cat 6A, Cat 7 and fibre optic
- System offers a convenient pathway for wires and cables
- Cost effective alternative to expensive cable tray
- Specially designed U-Hooks have large-diameter, rounded support surfaces
- Rounded edges help prevent over-bending and kinking of cables
- Alternative support option for MC/AC cable
- Compliant with NEC® and ANSI®/TIA structured cabling systems standards



Part Number	UTS200CATCM
Material	Steel
Finish	Electrogalvanized
Cable Capacity, Cat 5e	1,400
Cable Capacity, Cat 6	1,050
Cable Capacity, Cat 6A	650
Area	32 in <sup>2</sup>
Height (H)	12.65"
Length (L)	13.4"
Width (W)	2"
Hole Size (HS)	0.35"
A	8"
В	12"
Static Load (F)	200 lb
Standard Packaging Quantity	10 рс
UPC	78285699240

Cable capacity represents the total cable capacity for the assembly. The cable capacity for each U-Hook should not exceed half of the published cable capacity. Non-continuous supports may not exceed spacing of 5' (1.5 m) per TIA 569-C.9.7 and EN 50174-2.



ANSI is a registered trademark of American National Standards Institute. NEC is a registered trademark of, and National Electrical Code (NEC) standard is a copyright of the National Fire Protection Association, Inc.

## WARNING

New tproducts shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent 's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2020 nVent All rights reserved nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

