Universal Ground Rod Clamp, Rod to Conductor, Bronze - CP34











The nVent ERICO Universal acorn clamp line-up is a cost-effective and reliable way to connect ground rods to conductors throughout your grounding and bonding system. Suitable for both above ground and below grade installation, the clamp tightens the components together with tools that are available on every jobsite.

Now available in the most commonly requested universal size, you can carry less with you on the job and get more done.

When you're choosing your preferred connection method, make sure to reach out to our team with any technical questions or engineering needs.

- For use with copper-bonded ground rods
- Parts that are UL 467 Listed are suitable for direct burial in earth or concrete







Part Number	CP34
Material	Silicon Bronze
Ground Rod Diameter, Nominal	1/2" – 3/4"
Ground Rod Diameter, Actual (Ø)	0.50" – 0.68"
Conductor Size	#10 Solid - 1/0 Stranded 6 mm² Solid - 50 mm² Stranded
Rebar Size, Canada	10M
Rebar Size, Metric	12 mm
Rebar Size, US	#4
Wrench Size	1/2"
Complies With	IEC® EN 62561-1
Torque (TQ)	150 in lb
Certifications	CSA 46866 cULus
Standard Packaging Quantity	50 pc
UPC	78285630704
EAN-13	8711893041682



CSA, CSA-US and C-CSA-US are registered trademarks of Canadian Standards Association. IEC is a registered trademark of the International Electrotechnical Commission. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC. WARNING nevent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent 's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty. © 2020 nVent All rights reserved nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

ERICO